TIP TOP Oberflaechenschutz Elbe GmbH

Asplit® HGL Powder

Revision date: 20.04.2016 Revision No: 1,1

Product code: 00359-1175



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Asplit® HGL Powder

**Art.-No.** 592 0140

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

filler

### 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg
Telephone: +49(0)3491/635-50
Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@qbk-ingelheim.de

**1.4. Emergency telephone** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements:

Causes serious eye damage.

Causes skin irritation.

May cause damage to organs (lung) through prolonged or repeated exposure if inhaled.

# 2.2. Label elements

# Hazard components for labelling

Sodium silicate

Quartz

Signal word: Danger

Pictograms:



#### **Hazard statements**

H318 Causes serious eye damage.

H315 Causes skin irritation.

H373 May cause damage to organs (lung) through prolonged or repeated exposure if inhaled.

**Precautionary statements** 

P260 Do not breathe dust.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

2.3. Other hazards

Not known.

### **SECTION 3: Composition/information on ingredients**

Print date: 20.04.2016 GB - EN Page 1 of 7

TIP TOP Oberflaechenschutz Elbe GmbH

Asplit® HGL Powder

Revision date: 20.04.2016 Product code: 00359-1175 Revision No: 1,1



#### 3.2. Mixtures

### **Chemical characterization**

Mixture of the following substances with non-hazardous admixtures

### **Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
14808-60-7	Quartz			> 70 %
	238-878-4			
	STOT RE 2; H373			
1344-09-8	Sodium silicate			< 20 %
	215-687-4		01-2119448725-31	
	Skin Irrit. 2, Eye Dam. 1, STOT SE 3; H315 H318 H335			

Full text of H and EUH statements: see section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

### **General information**

Remove and wash contaminated clothing before re-use.

#### After inhalation

Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.

In the event of symptoms refer for medical treatment.

# After contact with skin

Wash with water and soap as a precaution.

Consult a doctor if skin irritation persists.

### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

# After ingestion

In the event of symptoms refer for medical treatment.

### 4.2. Most important symptoms and effects, both acute and delayed

May cause damage to organs through prolonged or repeated exposure. [lung]

Causes skin irritation.

Causes serious eye damage.

Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.

### Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

No data available.

### 5.3. Advice for firefighters

In case of fire, wear suitable respiratory equipment with positive air supply.

Protective suit.

# Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local

TIP TOP Oberflaechenschutz Elbe GmbH

### Asplit® HGL Powder

Revision date: 20.04.2016 Product code: 00359-1175 Revision No: 1,1



regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

In case of respirable dust, use a self-contained breathing apparatus.

Ensure adequate ventilation.

Use personal protective clothing.

# 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

### 6.3. Methods and material for containment and cleaning up

Pick up mechanically, avoiding dust, and provide disposal in suitable recipients.

Where possible recycling is preferred to disposal.

#### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

# Advice on safe handling

Keep container tightly closed.

Avoid the formation and deposition of dust.

Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

### Advice on protection against fire and explosion

No special protective measures against fire required.

# 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

# Advice on storage compatibility

No materials to be especially mentioned.

### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

filler

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

# Additional advice on limit values

Obey TLV for common dust, if applicable.

### 8.2. Exposure controls

### Appropriate engineering controls

Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

#### Protective and hygiene measures

Do not breathe dust.

Wash hands before breaks and at the end of workday.

When using do not eat, drink or smoke.

Remove and wash contaminated clothing before re-use.

# Eye/face protection

Safety goggles with side protection (EN 166).

# **Hand protection**

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

TIP TOP Oberflaechenschutz Elbe GmbH

#### Asplit® HGL Powder

Revision date: 20.04.2016 Product code: 00359-1175 Revision No: 1,1



Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

#### Skin protection

Long sleeved clothing (EN 368).

## Respiratory protection

Dust mask (EN 149)

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Powder
Colour: Beige
Odour: Odourless

### Changes in the physical state

Flash point: n.a. Lower explosion limits: n.a.

Upper explosion limits:

Ignition temperature: n.a.

Bulk density (at 20 °C): 1060 kg/m<sup>3</sup>

Water solubility: More or less insoluble

(at 20 °C)

### 9.2. Other information

No data available.

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No decomposition if stored and applied as directed.

#### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No hazardous reactions known.

### 10.4. Conditions to avoid

Not known.

### 10.5. Incompatible materials

No materials to be especially mentioned.

# 10.6. Hazardous decomposition products

No hazardous decomposition products known.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

# Irritation and corrosivity

Causes serious eye damage.

Causes skin irritation.

### Sensitising effects

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

TIP TOP Oberflaechenschutz Elbe GmbH

#### Asplit® HGL Powder

Revision date: 20.04.2016 Product code: 00359-1175 Revision No: 1,1



### Severe effects after repeated or prolonged exposure

May cause damage to organs (lung) through prolonged or repeated exposure if inhaled. (Quartz)

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### **Practical experience**

#### Other observations

Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecological data are not available.

#### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

# 12.6. Other adverse effects

Low hazard to waters.

## **Further information**

Do not flush into surface water or sanitary sewer system.

#### SECTION 13: Disposal considerations

# 13.1. Waste treatment methods

### Advice on disposal

It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

Where possible recycling is preferred to disposal.

#### Waste disposal number of waste from residues/unused products

080299

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

### **SECTION 14: Transport information**

## Land transport (ADR/RID); Marine transport (IMDG); Air transport (ICAO); Inland waterways transport (ADN):

#### 14.1. UN number:

No hazardous material as defined by the transport regulations.

# 14.2. UN proper shipping name:

No hazardous material as defined by the transport regulations.

# 14.3. Transport hazard class(es):

No hazardous material as defined by the transport regulations.

TIP TOP Oberflaechenschutz Elbe GmbH

Asplit® HGL Powder

Revision date: 20.04.2016 Revision No: 1,1

Product code: 00359-1175



#### 14.4. Packing group:

No hazardous material as defined by the transport regulations.

### 14.5. Environmental hazards

No hazardous material as defined by the transport regulations.

#### 14.6. Special precautions for user

No hazardous material as defined by the transport regulations.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No hazardous material as defined by the transport regulations.

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

2004/42/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

#### **SECTION 16: Other information**

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

# Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

H373 May cause damage to organs (lung) through prolonged or repeated exposure if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

#### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

TIP TOP Oberflaechenschutz Elbe GmbH

Asplit® HGL Powder

Revision date: 20.04.2016 Revision No: 1,1

Product code: 00359-1175



This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)