

according to Regulation (EC) No 1907/2006

## **TIP TOP FIXPASTE VC4-A**

Revision date: 24.02.2017 Product code: 00156-0111 Page 1 of 10

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TIP TOP FIXPASTE VC4-A

Art.-No.

516 9025, 516 9032, 516 9033, 516 9034, 516 9040, 516 9041, 516 9049, 516 9056, 516 9063, 516 9087

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Filler rubber

### 1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG
Street: Gruber Strasse 65
Place: D-85586 Poing
Telephone: +49 (0) 8121 / 707 - 100

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

**1.4. Emergency telephone** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2 Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

# 2.2. Label elements

# Regulation (EC) No. 1272/2008

# Hazard components for labelling

Naphtha (petroleum)

Signal word: Danger

Pictograms:







#### **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.



according to Regulation (EC) No 1907/2006

## **TIP TOP FIXPASTE VC4-A**

Revision date: 24.02.2017 Product code: 00156-0111 Page 2 of 10

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P273 Avoid release to the environment.

#### Special labelling of certain mixtures

EUH208 Contains N-(1,3-Dimethylbutyl)-N'-phenylenediamine. May produce an allergic

reaction.

# 2.3. Other hazards

Vapours may form explosive mixture with air.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### **Chemical characterization**

Preparation in aliphatic hydrocarbons

#### **Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to			
64742-49-0	Naphtha (petroleum) (Hyd	< 25 %		
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, H411			
64742-49-0	Naphtha (petroleum) (Hyd	< 10 %		
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, H411			
1314-13-2	Zinc oxide	< 2,5 %		
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic			
7704-34-9	sulfur	< 5 %		
	231-722-6	016-094-00-1	01-2119520616-43	
	Skin Irrit. 2; H315			
793-24-8	N-(1,3-Dimethylbutyl)-N'-	< 1 %		
	212-344-0		01-2119485839-15	
	Acute Tox. 4, Skin Sens.			

Full text of H and EUH statements: see section 16.

#### **Further Information**

According to note P to the regulation (EC) no. 1272/2008, "Naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures





according to Regulation (EC) No 1907/2006

#### **TIP TOP FIXPASTE VC4-A**

Revision date: 24.02.2017 Product code: 00156-0111 Page 3 of 10

#### **General information**

Remove contaminated soaked clothing immediately.

If you feel unwell, seek medical advice.

Take away from danger area and lay down affected person.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

Refer for medical treatment.

#### After contact with skin

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Summon a doctor immediately.

#### After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

May cause drowsiness or dizziness.

Attention. Beware, danger of aspiration.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

### Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

#### Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide, carbon dioxide, sulphur oxides and nitrogen oxides (NOx).

## 5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

### **Additional information**

Cool containers at risk with water spray jet.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Vapours are heavier than air and spread along ground.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.



according to Regulation (EC) No 1907/2006

## **TIP TOP FIXPASTE VC4-A**

Revision date: 24.02.2017 Product code: 00156-0111 Page 4 of 10

#### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

#### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed.

Keep a good ventilation and air-exhaust at the place of work.

Vapours are heavier than air and spread along ground.

## Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

## 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion protection rules.

## Advice on storage compatibility

Incompatible with oxidizing agents.

# Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Filler rubber

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL
1332-58-7	Kaolin respirable dust	-	2		TWA (8 h)	WEL
		-	_		STEL (15 min)	WEL

# 8.2. Exposure controls

## Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

### Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.



according to Regulation (EC) No 1907/2006

#### **TIP TOP FIXPASTE VC4-A**

Revision date: 24.02.2017 Product code: 00156-0111 Page 5 of 10

Remove and wash contaminated clothing before re-use.

#### Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

#### Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove < Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

#### Skin protection

Long sleeved clothing (EN 368).

### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: pasty
Colour: Black

Odour: Like petrol (gasoline)

Test method

### Changes in the physical state

Melting point:	< - 20 °C *)
Initial boiling point and boiling range:	60 - 95 °C *)
Flash point:	- 25 °C *)
Lower explosion limits:	1,0 vol. % *)
Upper explosion limits:	7,3 vol. % *)
Ignition temperature:	413 °C *)
Vapour pressure:	150 hPa *)

(at 20 °C)

Density (at 20 °C): 1,01 g/cm³ approx.

Water solubility: Immiscible

(at 20 °C)

Viscosity / kinematic: > 20,5 mm²/s

(at 40 °C)

Flow time: > 100 s 3 mm DIN/ISO 2431

Solvent separation test: < 3 % Solvent content: 30 - 35 %

## 9.2. Other information

\*) Naphtha (petroleum)

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No decomposition if stored and applied as directed.

# 10.2. Chemical stability



according to Regulation (EC) No 1907/2006

#### **TIP TOP FIXPASTE VC4-A**

Revision date: 24.02.2017 Product code: 00156-0111 Page 6 of 10

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Heating can release vapours which can be ignited.

Vapour/air-mixtures are explosive at intense warming.

#### 10.5. Incompatible materials

oxidizing agents

#### 10.6. Hazardous decomposition products

Carbon monoxide, carbon dioxide, sulphur oxides, and nitrogen oxides (NOx).

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

### **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

Naphtha (petroleum)

LD50/oral/rat: > 2000 mg/kg (Estimated)

LD50/dermal/rabbit: > 2000 mg/kg (Estimated)

LC50/inhalation/rat: > 20 mg/l (Estimated)

# Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Eye irritation: Not classified.

#### Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

# STOT-single exposure

May cause drowsiness or dizziness. ( (Naphtha (petroleum) (Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane)))

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### **Practical experience**

## Other observations

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

A longer or repeated contact my lead to irritation of eyes and mucous membranes.

Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons.

Attention. Beware, danger of aspiration!

## **SECTION 12: Ecological information**

#### 12.1. Toxicity



according to Regulation (EC) No 1907/2006

## **TIP TOP FIXPASTE VC4-A**

Revision date: 24.02.2017 Product code: 00156-0111 Page 7 of 10

Ecological data are not available.

Naphtha (petroleum)

LC50/EC50/EC50 : 1 - 10 mg/l (Estimated)
Toxic to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

#### 12.6. Other adverse effects

Low hazard to waters.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### Advice on disposal

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

## Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances

Classified as hazardous waste.

## Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for rause

Packaging that cannot be cleaned should be disposed of like the product.

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number:UN 113314.2. UN proper shipping name:Adhesives

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1

Limited quantity: 5 L / 30 kg
Excepted quantity: E1
Transport category: 3



according to Regulation (EC) No 1907/2006

## **TIP TOP FIXPASTE VC4-A**

Revision date: 24.02.2017 Product code: 00156-0111 Page 8 of 10

Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number:UN 113314.2. UN proper shipping name:Adhesives

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1

Limited quantity: 5 L / 30 kg Excepted quantity: E1

Marine transport (IMDG)

**14.1. UN number:** UN 1133

14.2. UN proper shipping name: Adhesives (Naphtha (petroleum))

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Marine pollutant: Yes
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
EmS: F-E, S-D

# Other applicable information (marine transport)

Receptacle max. 30 L, IMDG Code subsection 2.3.2.3

# Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:UN 113314.2. UN proper shipping name:Adhesives

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1

IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 30 L (\*)
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 30 L (\*)

# Other applicable information (air transport)

\*) [3.3.3.1 IATA DGR]

## 14.5. Environmental hazards



according to Regulation (EC) No 1907/2006

#### **TIP TOP FIXPASTE VC4-A**

Revision date: 24.02.2017 Product code: 00156-0111 Page 9 of 10

ENVIRONMENTALLY HAZARDOUS: yes



#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Naphtha (petroleum) (Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3%

n-hexane); Naphtha (petroleum) (Hydrocarbons, C6, isoalkanes, < 3% n-hexane)

2004/42/EC (VOC): 30 - 35 %

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 1 - slightly water contaminating

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## **SECTION 16: Other information**

# Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

# Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.



according to Regulation (EC) No 1907/2006

TIP TOP FIXPASTE VC4-A						
Revision date: 24.02.2017	Product code: 00156-0111	Page 10 of 10				
H302	Harmful if swallowed.					
H304	May be fatal if swallowed and enters airways.					
H315	Causes skin irritation.					
H317	May cause an allergic skin reaction.					
H336	May cause drowsiness or dizziness.					
H400	Very toxic to aquatic life.					
H410	Very toxic to aquatic life with long lasting effects.					
H411	Toxic to aquatic life with long lasting effects.					
EUH208	Contains N-(1,3-Dimethylbutyl)-N'-phenyl-p-phenylenediamine. May produce an allergic reaction.					

#### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)