TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP REMACOAT PR 100 SF Komp. A

Revision date: 16.09.2015 Revision No: 1,1

Product code: 00359-1133



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP REMACOAT PR 100 SF Komp, A

Art.-No.

590 2844, 590 2861

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coating component

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg
Telephone: +49(0)3491/635-50
Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@qbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements: Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazardous components which must be listed on the label

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Reaction product: bisphenol-F-epichlorine hydrine resins with average molecular weight <= 700

Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

1,6-Bis(2,3-epoxypropoxy)hexane

Signal word: Warning

Pictograms:



Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eve irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP REMACOAT PR 100 SF Komp. A

Revision date: 16.09.2015 Revision No: 1,1

Product code: 00359-1133



P362 Take off contaminated clothing.
P273 Avoid release to the environment.

Special labelling of certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

Not known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Epoxy resin based on bisphenol A and bisphenol F

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
25068-38-6	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)			< 70 %
	500-033-5	603-074-00-8	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
28064-14-4	Reaction product: bisphenol-F-epichlorine hydrine resins with average molecular weight <= 700			< 20 %
	500-108-2			
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
68609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.			< 20 %
	271-846-8	603-103-00-4	01-2119485289-22	
	Skin Irrit. 2, Skin Sens. 1; H315 H317			
16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexane			< 1 %
	240-260-4		01-2119463471-41	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

Causes serious eye irritation.

TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP REMACOAT PR 100 SF Komp. A

Revision date: 16.09.2015 Revision No: 1.1

Product code: 00359-1133



May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide and carbon dioxide

Phenoles

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Clean contaminated surface thoroughly.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Protect against direct sun radiation.

Advice on storage compatibility

Incompatible with:

Oxidizing agents

Amines

Acids and bases.

TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP REMACOAT PR 100 SF Komp. A

Revision date: 16.09.2015 Revision No: 1,1

Product code: 00359-1133



Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Coating component

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

No personal respiratory protective equipment normally required.

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Viscous liquid

Colour: Green

Odour: characteristic

Changes in the physical state

Initial boiling point and boiling range: > 200 °C
Flash point: > 100 °C
Lower explosion limits: n.d.
Ignition temperature: n.d.

Density (at 20 °C): 1,10 - 1,14 g/cm³ Water solubility: Immiscible

(at 20 °C)

Viscosity / dynamic: 800 - 1000 mPa·s

(at 25 °C)

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

Print date: 16.09.2015 GB - EN Page 4 of 8

TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP REMACOAT PR 100 SF Komp. A

Revision date: 16.09.2015 Revision No: 1.1

Product code: 00359-1133



10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents

Reactions with amines.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Protect against direct sun radiation.

Polymerisation occurs when exposed to heat.

10.5. Incompatible materials

Strong oxidizing agents

Acids and bases.

Amines

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Phenol

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction, (Reaction product; bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)), (Reaction product: bisphenol-F-epichlorine hydrine resins with average molecular weight <= 700), (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.),

(1,6-Bis(2,3-epoxypropoxy)hexane)

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Not readily biodegradable.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP REMACOAT PR 100 SF Komp. A

Revision date: 16.09.2015 Revision No: 1,1

Product code: 00359-1133



12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS

(PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and

sealants containing organic solvents or other hazardous substances

Classified as hazardous waste.

Contaminated packaging

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Epoxy resin, Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 9



Classification code: M6

Limited quantity: 5 L / 30 kg Excepted quantity: E1

Transport category: 3
Hazard No: 90
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Epoxy resin, Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 9



9

TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP REMACOAT PR 100 SF Komp. A

Revision date: 16.09.2015 Revision No: 1,1

Product code: 00359-1133

Classification code: M6

Limited quantity: 5 L / 30 kg

Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy

resin, Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.)

14.3. Transport hazard class(es): 9
14.4. Packing group: III

Hazard label:



Marine pollutant: Yes
Limited quantity: 5 L / 30 kg

Excepted quantity:

EmS: F-A, S-F

Air transport (ICAO)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy

resin, Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 9



Limited quantity Passenger: 30 kg G
Passenger LQ: Y964
Excepted quantity: E1

IATA-packing instructions - Passenger:964IATA-max. quantity - Passenger:450 LIATA-packing instructions - Cargo:964IATA-max. quantity - Cargo:450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment

restrictions for child bearing mothers and nursing.

Print date: 16.09.2015 GB - EN Page 7 of 8



TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP REMACOAT PR 100 SF Komp. A

Revision date: 16.09.2015 Revision No: 1,1

Product code: 00359-1133



Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)