// SERVICE  // MATERIAL PROCESSING  // SURFACE PROTECTION  // **AUTOMOTIVE**

# CORGHI AG TT 1600A
## TYRE CHANGER TRUCK

# CORGHI AG TT 1600A

- The new multi socket spindle, bead breaker disc inclination, 3 speed inverter motor and mobile console.
- Work tools always perpendicular to the wheel during all operations
- Base designed without a runway making it easier to access the work area.
- Demounting tool that facilitates the work on agricultural, deforestation and earthmoving tyres.
- Wheel and work tools always tangent and perpendicular to each other to permit maximum work precision and efficiency.
- Self-supporting base conceived to ensure free access to the work areas, wheel loading and unloading operations become extremely easy, considering that the runway has been eliminated.
- Wheel clamping using a hydraulic turntable.
- 9 direct clamp tilting positions, from 14" to 48" and with tilting up to 58". Possibility to clamp rims with a minimum hole of 90 mm.
- Hydraulic bead breaker disc, which permits setting the perfect inclination while working.
- Ergonomic controls and equipped with wheels to move the trolley type console.
- Turntable operated by a 3 speed motor invertor, including a low speed for tyre retreading operations.

| | |
|---|---|
| Bead breaking maximum lengthways force on inside | 30000 N |
| Bead breaking maximum lengthways force on outside | 25000 N |
| Hydraulic lengthways stroke | 1045 mm |
| Maximum clamping capacity | 14 - 58 Inch |
| Clamping force | 59200 N |
| Tyre diameter | 2500 mm |
| Tyre width | 1600 mm |
| Wheel weight | liftable 2.500 kg while working 1,700 kg |
| Wheel central hole minimum | 90 mm |
| Adjustable hydraulic pressure | 80 - 180 bar |
| Power supply | 400v/3ph/50hz |
| Weight | 1300 Kg |

| Ref. No. | Description | Content |
|---|---|---|
| AG TT 1600A | CORGHI AG TT 1600A | 1 |

FINANCE OPTIONS

SERVICE CONTRACTS

ACCESSORIES

2 YEAR WARRANTY

FREE DELIVERY AND INSTALLATION

CORGHI exclusively distributed by REMA TIP TOP in **Great Britain**