

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SC-BL

Revision date: 04.09.2019

Product code: 00156-0083

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP CEMENT SC-BL

Art.-No.

506 0160, 506 0170, 506 0351, 506 0352, 506 4357, 506 4550, 506 4560, 510 1155, 510 1156, 510 1165, 510 1832, 510 1833, 510 1848, 510 1849, 510 3256, 510 3257, 510 3304, 510 3407, 510 3408, 510 3438, 510 3500, 510 3501, 510 3517, 510 3603, 510 3610, 510 3710, 514 1150, 514 1591, 514 3113, 514 4740, 515 9152, 515 9303, 515 9327, 515 9328, 515 9329, 515 9334, 515 9335, 515 9336, 515 9337, 515 9341, 515 9342, 515 9358, 515 9359, 515 9365, 515 9366, 515 9388, 515 9389, 515 9396, 515 9397, 515 9405, 515 9406, 515 9407, 516 9025, 516 9033, 516 9040, 516 9087, 599 2200

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesive

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG
Street: Gruber Strasse 65
Place: D-85586 Poing
Telephone: +49 (0) 8121 / 707 - 100
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number: INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard Statements:
Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Ethyl acetate
Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P101 If medical advice is needed, have product container or label at hand.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SC-BL

Revision date: 04.09.2019

Product code: 00156-0083

Page 2 of 11

P210 P260 P280 P303+P361+P353 P305+P351+P338 P312 P273 P501	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapour. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. Avoid release to the environment. Dispose of contents/container to waste treatment facility in accordance with local and national regulations .
--	---

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.
 Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation with ethyl acetate

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
141-78-6	Ethyl acetate	< 65 %
	205-500-4	
	607-022-00-5	
	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066	
92062-15-2	Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane [Solvent naphta (petroleum)]	< 25 %
	926-605-8	
	01-2119486291-36	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411	
14634-93-6	Zinc-bis (N-ethyl-N-phenyldithiocarbamate)	< 5 %
	238-677-1	
	Eye Irrit. 2, Aquatic Chronic 4; H319 H413	
5459-93-8	N-Cyclohexyl-N-ethylamine	< 1 %
	226-733-8	
	01-2119949285-29	
	Flam. Liq. 3, Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Aquatic Chronic 3; H226 H311 H332 H302 H314 H318 H412	
1314-13-2	Zinc oxide	< 1 %
	215-222-5	
	030-013-00-7	
	01-2119463881-32	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410	

Full text of H and EUH statements: see section 16.

Further Information

According to note P to the regulation (EC) no. 1272/2008, "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 %



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SC-BL

Revision date: 04.09.2019

Product code: 00156-0083

Page 3 of 11

by weight.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

- Remove contaminated soaked clothing immediately.
- If you feel unwell, seek medical advice.
- Take away from danger area and lay down affected person.

After inhalation

- Move to fresh air in case of accidental inhalation of vapours or decomposition products.
- In the event of symptoms refer for medical treatment.

After contact with skin

- Wash off with soap and plenty of water.
- Consult a doctor if skin irritation persists.

After contact with eyes

- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Seek medical treatment by eye specialist.

After ingestion

- Do not induce vomiting.
- Summon a doctor immediately.
- Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

- Causes serious eye irritation.
- May cause drowsiness or dizziness.
- Repeated exposure may cause skin dryness or cracking.
- Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

- Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

- Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

- Full water jet.

5.2. Special hazards arising from the substance or mixture

- Fire may produce:
carbon monoxide and carbon dioxide

5.3. Advice for firefighters

- Use breathing apparatus with independent air supply.
- Protective suit.

Additional information

- Vapours are heavier than air and spread along ground.
- The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
- Cool containers at risk with water spray jet.
- Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SC-BL

Revision date: 04.09.2019

Product code: 00156-0083

Page 4 of 11

In case of vapour formation use respirator.
Use only explosion-proof equipment.
Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.
Vapours are heavier than air and spread along ground.
Keep a good ventilation and air-exhaust at the place of work.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.
Do not smoke.
Take precautionary measures against static discharges.
Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.
Pay attention to anti-explosion rules.

Hints on joint storage

Incompatible with:
Oxidizing agents
Nitrous acid and other nitrosating agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL

8.2. Exposure controls



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SC-BL

Revision date: 04.09.2019

Product code: 00156-0083

Page 5 of 11

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Splash protection:

Protective gloves resistant to chemicals made off natural-rubber latex, minimum coat thickness 0.6 mm, permeation resistance (wear duration) approx. 10 minutes, i.e. protective glove <Lapren 706> made by www.kcl.de.

Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance (wear duration) > 60 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Viscous liquid
Colour: Blue
Odour: Ester-like

Test method

pH-Value: n.d.

Changes in the physical state

Melting point: n.d.

Initial boiling point and boiling range: > 35 °C

Sublimation point: n.a.

Softening point: n.d.

Flash point: - 20 °C DIN EN ISO 3679

Flammability

Solid: n.a.

Gas: n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: 2,1 vol. %

Upper explosion limits: 11,5 vol. %

Ignition temperature: 460 °C

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SC-BL

Revision date: 04.09.2019

Product code: 00156-0083

Page 6 of 11

Auto-ignition temperatureSolid: n.a.
Gas: n.a.

Decomposition temperature: n.d.

Oxidizing properties

Not oxidising.

Vapour pressure: 100 hPa
(at 20 °C)Density (at 20 °C): 0,88 g/cm³

Bulk density: n.a.

Water solubility: Immiscible
(at 20 °C)**Solubility in other solvents**

n.d.

Partition coefficient: n.d.

Viscosity / dynamic: 4500 - 6500 mPa·s
(at 20 °C)Viscosity / kinematic: 3740 - 3820 mm²/s
(at 40 °C)Flow time: 385 s 6 DIN EN ISO 2431
(at 23 °C)

Vapour density: n.d.

Evaporation rate: n.d.

Solvent separation test: < 3%

Solvent content: < 85 %

9.2. Other information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoidTo avoid thermal decomposition, do not overheat.
Vapour/air mixtures are explosive at intensive warming.
Heating can release vapours which can be ignited.**10.5. Incompatible materials**Nitrous acid and other nitrosating agents.
oxidizing agents**10.6. Hazardous decomposition products**Carbon monoxide and carbon dioxide
An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SC-BL

Revision date: 04.09.2019

Product code: 00156-0083

Page 7 of 11

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.
No toxicological data available.

Irritation and corrosivity

Causes serious eye irritation.
Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Ethyl acetate; Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane [Solvent naphta (petroleum)])

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Effects of breathing high concentrations of vapour may include: Headache, dizziness, weakness, unconsciousness.
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Further information

An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.
Toxic to aquatic life with long lasting effects.
Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane
LC50/EC50/EC50 : 1 - 10 mg/l
Zinc oxide
EC50/Ceriodaphnia dubia/48 h = 0,01 - 0,1 mg/l
EC50/Selenastrum capricornutum/72 h = 0,01 - 0,1 mg/l
N-Cyclohexyl-N-ethylamine
EC50/Daphnia magna/48 h = 10 - 100 mg/l
ErC50/Desmodesmus subspicatus/72 h = 10 - 100 mg/l
N-(1,3-Dimethylbutyl)-N'-phenyl-p-phenylenediamine
Ethyl acetate
LC50/EC50/EC50 : > 100 mg/l

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SC-BL

Revision date: 04.09.2019

Product code: 00156-0083

Page 8 of 11

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.
Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.
Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1133
<u>14.2. UN proper shipping name:</u>	Adhesives
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	III
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Transport category:	3
Tunnel restriction code:	E

Inland waterways transport (ADN)

<u>14.1. UN number:</u>	UN 1133
<u>14.2. UN proper shipping name:</u>	Adhesives
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	III

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SC-BL

Revision date: 04.09.2019

Product code: 00156-0083

Page 9 of 11

Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives (Solvent naphtha (petroleum))
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: Yes
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
EmS: F-E, S-D

Other applicable information (marine transport)

Receptacle max. 450 L, IMDG Code subsection 2.3.2.2
Segregation group: -

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 30 L (*)
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 100 L (*)

Other applicable information (air transport)

*) [3.3.3.1 IATA DGR]

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes





Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SC-BL

Revision date: 04.09.2019

Product code: 00156-0083

Page 10 of 11

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC):	80 - 85 %
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
--------------------------	--

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SC-BL

Revision date: 04.09.2019

Product code: 00156-0083

Page 11 of 11

H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)