TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP COROFLAKE 60 B

Revision date: 13.10.2015 Revision No: 1,1

Product code: 00359-1036



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP COROFLAKE 60 B

Art.-No. 590 0916

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hardener

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg
Telephone: +49(0)3491/635-50
Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1

Reproductive toxicity: Repr. 1B

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Causes severe skin burns and eye damage.

May cause an allergic skin reaction. May damage the unborn child.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazardous components which must be listed on the label

3-aminomethyl-3,5,5-trimethylcyclohexylamine

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)

1,3-Diaza-2,4-cyclopentadiene

Signal word: Danger

Pictograms:



Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.
H360D May damage the unborn child.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP COROFLAKE 60 B

Revision date: 13.10.2015 Revision No: 1.1

Product code: 00359-1036



P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P273 Avoid release to the environment.

Store locked up. Special labelling of certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Restricted to professional users.

2.3. Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

P405

Chemical characterization

Preparation contains epoxy resins and polyamines

Hazardous components

CAS No	Chemical name	Quantity			
	EC No	Index No	REACH No		
	Classification according to				
100-51-6	benzyl alcohol	< 15 %			
	202-859-9	603-057-00-5	01-2119492630-38		
	Acute Tox. 4, Acute Tox. 4				
2855-13-2	3-Aminomethyl-3,5,5-trime	< 10 %			
	220-666-8	612-067-00-9	01-2119514687-32		
	Acute Tox. 4, Acute Tox. 4 H317 H412				
25513-64-8	2,2,4(or 2,4,4)-trimethylhe	< 10 %			
	247-063-2		01-2119569598-25		
	Acute Tox. 4, Skin Corr. 1I				
25068-38-6	Epoxy resin (number aver (epichlorhydrin)	< 10 %			
	500-033-5	603-074-00-8	01-2119456619-26		
	Skin Irrit. 2, Eye Irrit. 2, Sk				
288-32-4	1,3-Diaza-2,4-cyclopentac	< 1 %			
	206-019-2		01-2119485825-24		
	Repr. 1B, Acute Tox. 4, Sk				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

Call a physician immediately.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.

After contact with skin

In case of contact with skin wash off immediately with plenty of water.

Seek medical treatment immediately.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP COROFLAKE 60 B

Revision date: 13.10.2015 Product code: 00359-1036 Revision No: 1,1



Summon a doctor immediately.

After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

May cause harm to the unborn child.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

6.2. Environmental precautions

Clean contaminated surface thoroughly.

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Handle and open container with care.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP COROFLAKE 60 B

Revision date: 13.10.2015 Product code: 00359-1036 Revision No: 1,1



Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Advice on storage compatibility

Incompatible with:

Oxidizing agents

Amines

Acids and bases.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
12001-26-2	Mica, respirable	-	0.8		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Yellowish
Odour: Mild

Print date: 13.10.2015 GB - EN Page 4 of 9

TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP COROFLAKE 60 B

Revision date: 13.10.2015 Revision No: 1,1

Product code: 00359-1036



Changes in the physical state

Flash point: > 100 °C
Lower explosion limits: n.d.
Ignition temperature: n.d.

Density (at 20 °C): 1,25 g/cm³ Water solubility: Immiscible

Viscosity / dynamic: 1100 - 1500 mPa·s

(at 25 °C)

Flow time: > 40 s 6 DIN/ISO 2431

(at 25 °C)

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents

Reactions with amines.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

10.5. Incompatible materials

oxidizing agents

Acids and bases.

Amines

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

Ammonia

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available. ATEmix/oral: > 2000 mg/kg ATEmix/dermal: > 2000 mg/kg

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

May cause an allergic skin reaction. (3-Aminomethyl-3,5,5-trimethylcyclohexylamine), (2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine), (Epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin))

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

May damage the unborn child. (1,3-Diaza-2,4-cyclopentadiene)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no

TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP COROFLAKE 60 B

Revision date: 13.10.2015 Product code: 00359-1036 Revision No: 1,1



1272/2008.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

LC50/Oncorhynchus mykiss/96 h = 2 mg/l EC50/Daphnia magna/48 h = 1,8 mg/l

ErC50/Scenedesmus capricornutum/72 h = 11 mg/l

12.2. Persistence and degradability

Not readily biodegradable.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances

Classified as hazardous waste.

Contaminated packaging

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.

8

(3-Aminomethyl-3,5,5-trimethylcyclohexylamine, 2,2,4(or

2,4,4)-trimethylhexane-1,6-diamine)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 8



Classification code: C7

TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP COROFLAKE 60 B

Revision date: 13.10.2015 Revision No: 1.1

Product code: 00359-1036

Limited quantity: 5 L / 30 kg **Excepted quantity:** E1 Transport category: 3

Hazard No: 80 Ε Tunnel restriction code:

Inland waterways transport (ADN)

UN 2735 14.1. UN number:

AMINES, LIQUID, CORROSIVE, N.O.S. 14.2. UN proper shipping name:

(3-Aminomethyl-3,5,5-trimethylcyclohexylamine, 2,2,4(or

2,4,4)-trimethylhexane-1,6-diamine)

14.3. Transport hazard class(es): Ш 14.4. Packing group:

Hazard label:

Classification code:

Limited quantity: 5 L / 30 ka

Excepted quantity: E1

Marine transport (IMDG)

UN 2735 14.1. UN number:

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorone diamine and

trimethylhexane diamine)

14.3. Transport hazard class(es):

14.4. Packing group: Ш Hazard label:



Marine pollutant: No Limited quantity: 5 L / 30 kg Excepted quantity: F-A, S-B

Air transport (ICAO)

EmS:

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorone diamine and

trimethylhexane diamine)

14.3. Transport hazard class(es): 8 Ш 14.4. Packing group:

Hazard label:



Limited quantity Passenger: Passenger LQ: Y841 Excepted quantity: E1

IATA-packing instructions - Passenger: 852 IATA-max. quantity - Passenger: 5 L IATA-packing instructions - Cargo: 856 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no





TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP COROFLAKE 60 B

Revision date: 13.10.2015 Product code: 00359-1036 Revision No: 1,1



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment

restrictions for child bearing mothers and nursing.

Water contaminating class (D):

2 - water contaminating

Additional information

Consider Chemical prohibition regulation.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H360D May damage the unborn child.

H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

TIP TOP Oberflaechenschutz Elbe GmbH

TIP TOP COROFLAKE 60 B

Revision date: 13.10.2015 Revision No: 1,1

Product code: 00359-1036



The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the

legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)