

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

TIP TOP COROPUR SLIDING AGENT

**Art.-No.**

580 0779

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of the substance/mixture**

Protection against corrosion

### 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

### 1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24  
24

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Flammable liquid: Flam. Liq. 3

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Flammable liquid and vapour.

Causes skin irritation.

Harmful if inhaled.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

**Hazard components for labelling**

Xylene (mixed isomers)

Ethyl benzene

Signal word:

Warning

Pictograms:



**Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take precautionary measures against static discharge.

P260 Do not breathe vapour.

**TIP TOP COROPUR SLIDING AGENT**

Revision date: 20.01.2016

Revision No: 1,0

Product code: 00359-1263



P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P314	Get medical advice/attention if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container to in accordance with local and national regulations.

**2.3. Other hazards**

Vapours may form explosive mixture with air.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Polyether

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
1330-20-7	Xylene (mixed isomers)			25 - 50 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H312 H332 H315			
64742-95-6	Solvent naphta (petroleum)			5 - 10 %
	918-668-5	649-356-00-4	01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
100-41-4	Ethyl benzene			10 - 12,5 %
	202-849-4	601-023-00-4	01-2119489370-35	
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
108-94-1	Cyclohexanone			2,5 - 5 %
	203-631-1	606-010-00-7	01-2119453616-35	
	Flam. Liq. 3, Acute Tox. 4; H226 H332			
122-99-6	2-Phenoxyethanol			2,5 - 5 %
	204-589-7	603-098-00-9	01-2119488943-21	
	Acute Tox. 4, Eye Irrit. 2; H302 H319			

Full text of H and EUH statements: see section 16.

**Further Information**

According to note P to the regulation (EC) no. 1272/2008, "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.  
Take away from danger area and lay down affected person.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours or decomposition products.  
Keep warm and calm injured person.  
If patient is not breathing, apply artificial respiration.  
Seek medical treatment immediately.

**After contact with skin**

In case of contact with skin wash off immediately with soap and water.  
Do not use solvents or thinners.



Consult a doctor if skin irritation persists.

**After contact with eyes**

Remove contact lens.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

**After ingestion**

Do not induce vomiting.

Rinse mouth.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

**4.2. Most important symptoms and effects, both acute and delayed**

Harmful if inhaled.

Causes skin irritation.

May cause damage to organs through prolonged or repeated exposure.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

---

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

**Unsuitable extinguishing media**

Full water jet.

**5.2. Special hazards arising from the substance or mixture**

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>).

High smoke development

**5.3. Advice for firefighters**

In case of fire, wear suitable respiratory equipment with positive air supply.

Protective suit.

**Additional information**

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.

Keep away sources of ignition.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

**6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

**6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Clean contaminated surface thoroughly.

**6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.



## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Do not wear contact lenses when handling the product.  
 Keep container tightly closed.  
 Vapours are heavier than air and spread along ground.  
 Keep a good ventilation and air-exhaust at the place of work.  
 Do not empty container under pressure. No pressure tank!

#### Advice on protection against fire and explosion

Keep away from heat and sources of ignition.  
 Do not smoke.  
 Take precautionary measures against static discharges.  
 Use only explosion-proof equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.  
 Pay attention to anti-explosion rules.  
 Take precautionary measures against static discharges.  
 Storage temperature between 15°C to 30°C

#### Advice on storage compatibility

Incompatible with:  
 Strong oxidizing agents  
 strong acids and strong bases

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Protection against corrosion

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
108-94-1	Cyclohexanone	10	41		TWA (8 h)	WEL
		20	82		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-94-1	Cyclohexanone	cyclohexanol	2 mmol/mol	urine	Post shift
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

### 8.2. Exposure controls

#### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

#### Protective and hygiene measures

Do not inhale vapours.  
 Wash hands before breaks and immediately after handling the product.



When using do not eat, drink or smoke.  
Avoid contact with skin, eyes and clothing.  
Remove and wash contaminated clothes before re-use.

**Eye/face protection**

Tightly fitting goggles (EN 166).

**Hand protection**

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Skin protection**

Solvent-resistant apron (EN 467).

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

---

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Various
Odour:	characteristic

**Changes in the physical state**

Flash point:	40 °C	DIN 53213
Lower explosion limits:	3,0 vol. %	
Upper explosion limits:	9,4 vol. %	
Ignition temperature:	425 °C	
Vapour pressure: (at 20 °C)	5,18 hPa	
Density (at 20 °C):	0,92 g/cm <sup>3</sup>	
Water solubility:	Immiscible	
Viscosity / kinematic: (at 40 °C)	> 20,5 mm <sup>2</sup> /s	
Solvent content:	70 %	

**9.2. Other information**

No data available.

---

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with acids, alkalies and oxidizing agents

**10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.  
Vapour/air mixtures are explosive at intensive warming.  
Heating can release vapours which can be ignited.

**10.5. Incompatible materials**

Strong oxidizing agents.  
Strong acids and strong bases



---

### **10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

---

## **SECTION 11: Toxicological information**

### **11.1. Information on toxicological effects**

#### **Acute toxicity**

Harmful if inhaled.

No toxicological data available.

#### **Irritation and corrosivity**

Causes skin irritation.

Eye irritation: Not classified.

#### **Sensitising effects**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

Based on available data, the classification criteria are not met.

#### **Severe effects after repeated or prolonged exposure**

May cause damage to organs through prolonged or repeated exposure. (Ethyl benzene)

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### **Practical experience**

#### **Other observations**

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Components of the product may be absorbed into the body through the skin.

Contact with eyes may cause irritation.

Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

Attention. Beware, danger of aspiration!

---

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

### **12.2. Persistence and degradability**

No data available.

### **12.3. Bioaccumulative potential**

No data available.

### **12.4. Mobility in soil**

No data available.

### **12.5. Results of PBT and vPvB assessment**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

### **12.6. Other adverse effects**

Hazardous water pollutant.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

---

## **SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Advice on disposal**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

**Waste disposal number of waste from residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances  
Classified as hazardous waste.

**Contaminated packaging**

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

Empty containers should be taken for local recycling, recovery or waste disposal.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (Xylene (mixed isomers), Ethyl benzene)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L / 30 kg  
 Excepted quantity: E1  
 Transport category: 3  
 Hazard No: 30  
 Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (Xylene (mixed isomers), Ethyl benzene)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L / 30 kg  
 Excepted quantity: E1

**Marine transport (IMDG)**

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (xylene, ethylbenzene)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Marine pollutant: No  
 Limited quantity: 5 L / 30 kg  
 Excepted quantity: E1  
 EmS: F-E, S-E

**Air transport (ICAO)**

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (xylene, ethylbenzene, mixture)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Limited quantity Passenger: 10 L  
 Passenger LQ: Y344  
 Excepted quantity: E1  
 IATA-packing instructions - Passenger: 355  
 IATA-max. quantity - Passenger: 60 L  
 IATA-packing instructions - Cargo: 366  
 IATA-max. quantity - Cargo: 220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

The transport takes place only in approved and appropriate packaging.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

2004/42/EC (VOC): 644 g/l

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - water contaminating

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information**

**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk



**TIP TOP COROPUR SLIDING AGENT**

Revision date: 20.01.2016

Revision No: 1,0

Product code: 00359-1263



GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*