



# Safety Data Sheet

according to Regulation (EC) No 1907/2006


## TIP TOP PRIMER HG 2

Revision date: 03.07.2019

Product code: 00359-1082

Page 2 of 11

### Pictograms:



### Hazard statements

H226	Flammable liquid and vapour.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

### Precautionary statements

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P403+P235	Store in a well-ventilated place. Keep cool.

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.  
Vapours may form explosive mixture with air.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Polymer in organic solvent

#### Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	GHS Classification	
	Reaction mass of ethylbenzene and xylene	50 - 80 %
		01-2119488216-32
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304	
85535-85-9	Alkanes, C14-17, chloro; chlorinated paraffins, C14-17	< 10 %
	287-477-0	602-095-00-X
		01-2119519269-33
	Lact., Aquatic Acute 1, Aquatic Chronic 1; H362 H400 H410 EUH066	
108-88-3	Toluene	< 1 %
	203-625-9	601-021-00-3
		01-2119471310-51
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H319 H336 H373 H304 H412	

Full text of H and EUH statements: see section 16.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP PRIMER HG 2

Revision date: 03.07.2019

Product code: 00359-1082

Page 3 of 11

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.  
Take away from danger area and lay down affected person.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours.  
Seek medical treatment immediately.

#### After contact with skin

Wash off with soap and plenty of water.  
Possible risk of resorption through skin.  
Consult a doctor if skin irritation persists.

#### After contact with eyes

Remove contact lens.  
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical treatment by eye specialist.

#### After ingestion

Do not induce vomiting.  
Rinse out mouth and give plenty of water to drink.  
Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.  
Induce vomiting only upon the advice of a physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Harmful in contact with skin or if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure.  
May cause harm to breastfed babies.  
Attention. Beware, danger of aspiration.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.  
Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

#### Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire may produce:  
Carbon monoxide, carbon dioxide, sulphur oxides, and nitrogen oxides (NO<sub>x</sub>).  
Hydrogen chloride (HCl)  
Chlorine and traces of phosgene.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP PRIMER HG 2

Revision date: 03.07.2019

Product code: 00359-1082

Page 4 of 11

#### Additional information

- Cool containers at risk with water spray jet.
- Flashback at a long distance is possible.
- Vapours are heavier than air and spread along ground.
- The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
- Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- In case of vapour formation use respirator.
- Use only explosion-proof equipment.
- Ensure adequate ventilation.
- Remove persons to safety.
- Use personal protective clothing.

#### 6.2. Environmental precautions

- Do not discharge into the drains/surface waters/ground water.
- Do not discharge into the subsoil/soil.

#### 6.3. Methods and material for containment and cleaning up

- Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
- Shovel into suitable container for disposal.
- Clean contaminated surface thoroughly.

#### 6.4. Reference to other sections

- Observe protective instructions (see Sections 7 and 8).
- Information for disposal see section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

- Keep container tightly closed.
- Vapours are heavier than air and spread along ground.
- Keep a good ventilation and air-exhaust at the place of work.
- Avoid contact with skin, eyes and clothing.

##### Advice on protection against fire and explosion

- Keep away from heat and sources of ignition.
- Do not smoke.
- Take precautionary measures against static discharges.
- Use only explosion-proof equipment.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

- Keep container tightly closed in a dry, cool and well-ventilated place.
- Pay attention to anti-explosion rules.

##### Hints on joint storage

- Incompatible with oxidizing agents.

##### Further information on storage conditions

- Keep away from food, drink and animal feeding stuffs.

#### 7.3. Specific end use(s)

- Primer Coat

### SECTION 8: Exposure controls/personal protection

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP PRIMER HG 2**

Revision date: 03.07.2019

Product code: 00359-1082

Page 5 of 11

**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**8.2. Exposure controls****Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Protective and hygiene measures**

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

**Eye/face protection**

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

**Hand protection**

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

**Skin protection**

Solvent-resistant apron (EN 467).

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: Liquid  
Colour: Black  
Odour: Aromatic

**Test method**

pH-Value: n.d.

**Changes in the physical state**

Melting point: n.d.

Initial boiling point and boiling range: n.d.

Sublimation point: n.a.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP PRIMER HG 2**

Revision date: 03.07.2019

Product code: 00359-1082

Page 6 of 11

Softening point: n.d.

Flash point: 25 °C

**Flammability**

Solid: n.a.

Gas: n.a.

**Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: n.d.

Upper explosion limits: n.d.

Ignition temperature: 460 °C \*)

**Auto-ignition temperature**

Solid: n.a.

Gas: n.a.

Decomposition temperature: n.d.

**Oxidizing properties**

Not oxidising.

Vapour pressure: n.d.

Density (at 20 °C): 0,93 - 0,97 g/cm<sup>3</sup>

Bulk density: n.a.

Water solubility:  
(at 20 °C) Immiscible**Solubility in other solvents**

n.d.

Partition coefficient: n.d.

Viscosity / dynamic:  
(at 25 °C) 500 - 600 mPa·s BrookfieldViscosity / kinematic:  
(at 40 °C) > 20,5 mm<sup>2</sup>/s

Flow time: n.d.

Vapour density: n.d.

Evaporation rate: n.d.

Solvent separation test: 0 %

Solvent content: &lt; 80 %

**9.2. Other information**

\*) Xylene (mixed isomers)

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with strong oxidizing agents.

**10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP PRIMER HG 2**

Revision date: 03.07.2019

Product code: 00359-1082

Page 7 of 11

Vapour/air mixtures are explosive at intensive warming.  
Heating can release vapours which can be ignited.

**10.5. Incompatible materials**

Strong oxidizing agents.

**10.6. Hazardous decomposition products**

Fire may produce:  
Carbon monoxide, carbon dioxide, sulphur oxides, and nitrogen oxides (NO<sub>x</sub>).  
Hydrogen chloride (HCl)  
Chlorine and traces of phosgene.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

Harmful in contact with skin.  
Harmful if inhaled.  
No toxicological data available.  
ATEmix/dermal: ~ 1550 mg/kg  
ATEmix/inhalation: ~ 15 mg/l/4 h

**Irritation and corrosivity**

Causes skin irritation.  
Causes serious eye irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

May cause harm to breast-fed children. (Alkanes, C14-17, chloro; chlorinated paraffins, C14-17)  
Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.  
Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (Reaction mass of ethylbenzene and xylene)

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (Reaction mass of ethylbenzene and xylene)

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

**Practical experience****Other observations**

Inhalation of vapours is irritating to the respiratory system, may cause throat pain and cough.  
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.  
Possible risk of resorption through skin.  
Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.  
Attention. Beware, danger of aspiration.  
May cause sensitization of susceptible persons by skin contact.

**SECTION 12: Ecological information****12.1. Toxicity**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP PRIMER HG 2

Revision date: 03.07.2019

Product code: 00359-1082

Page 8 of 11

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

#### **12.2. Persistence and degradability**

No data available

#### **12.3. Bioaccumulative potential**

No data available

#### **12.4. Mobility in soil**

No data available

#### **12.5. Results of PBT and vPvB assessment**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

#### **12.6. Other adverse effects**

Hazardous water pollutant.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Advice on disposal**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

##### **Waste disposal number of waste from residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### **Contaminated packaging**

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

Empty containers should be taken for local recycling, recovery or waste disposal.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

<b><u>14.1. UN number:</u></b>	UN 1133
<b><u>14.2. UN proper shipping name:</u></b>	Adhesives
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	III
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP PRIMER HG 2

Revision date: 03.07.2019

Product code: 00359-1082

Page 9 of 11

#### Inland waterways transport (ADN)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1

#### Marine transport (IMDG)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives (Alkanes, C14-17, chloro, chlorinated paraffines, C14-17)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Marine pollutant: Yes  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1  
EmS: F-E, S-D

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes





## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP PRIMER HG 2

Revision date: 03.07.2019

Product code: 00359-1082

Page 10 of 11

#### **14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

#### **14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

The transport takes place only in approved and appropriate packaging.

### **SECTION 15: Regulatory information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 48: Toluene

2004/42/EC (VOC): < 80 %

##### **National regulatory information**

Employment restrictions:

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### **15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

### **SECTION 16: Other information**

#### **Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

#### **Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP PRIMER HG 2**

Revision date: 03.07.2019

Product code: 00359-1082

Page 11 of 11

H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*