

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SOLUTION 12250 D

Revision date: 12.06.2019

Product code: 00156-0437

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SOLUTION 12250 D

Art.-No.

536 6000, 536 6020, 538 1350

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesive

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG

Street: Gruber Strasse 65

Place: D-85586 Poing

Telephone: +49 (0) 8121 / 707 - 100

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone

number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Aspiration hazard: Asp. Tox. 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008**Hazard components for labelling**

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

Ethyl acetate

Signal word:

Danger

Pictograms:**Hazard statements**

H225

Highly flammable liquid and vapour.

H304

May be fatal if swallowed and enters airways.

H315

Causes skin irritation.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SOLUTION 12250 D

Revision date: 12.06.2019

Product code: 00156-0437

Page 2 of 10

- H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P261 Avoid breathing vapour.
P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352 IF ON SKIN: Wash with plenty of water.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P312 Call a POISON CENTER/doctor if you feel unwell.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to in accordance with local and national regulations.

Special labelling of certain mixtures

- EUH208 Contains Colophony. May produce an allergic reaction.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.
Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Preparation in aliphatic hydrocarbons

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes			50 - 100 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
141-78-6	Ethyl acetate			25 - 50 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
1314-13-2	Zinc oxide			< 0,5 %
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
8050-09-7	Colophony			< 0,5 %
	232-475-7	650-015-00-7	01-2119480418-32	
	Skin Sens. 1; H317			

Full text of H and EUH statements: see section 16.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

SOLUTION 12250 D

Revision date: 12.06.2019

Product code: 00156-0437

Page 3 of 10

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

- Remove contaminated soaked clothing immediately.
- In the event of persistent symptoms receive medical treatment.
- Take away from danger area and lay down affected person.

After inhalation

- Move to fresh air in case of accidental inhalation of vapours.
- If you feel unwell, seek medical advice.

After contact with skin

- Wash off with soap and plenty of water.
- Consult a doctor if skin irritation persists.

After contact with eyes

- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Seek medical treatment by eye specialist.

After ingestion

- Do not induce vomiting.
- Summon a doctor immediately.
- Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

- Causes skin irritation.
- Causes serious eye irritation.
- May cause drowsiness or dizziness.
- May be fatal if swallowed and enters airways. Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

- Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

- Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

- Full water jet.

5.2. Special hazards arising from the substance or mixture

- Fire may produce:
carbon monoxide and carbon dioxide

5.3. Advice for firefighters

- Use breathing apparatus with independent air supply.
- Protective suit.

Additional information

- Vapours are heavier than air and spread along ground.
- The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
- Cool containers at risk with water spray jet.
- Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- In case of vapour formation use respirator.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SOLUTION 12250 D

Revision date: 12.06.2019

Product code: 00156-0437

Page 4 of 10

Use only explosion-proof equipment.
Avoid contact with skin, eyes and clothing.
Ensure adequate ventilation.
Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.
Inform competent authority about release into the sewage, ground or into waters.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal see section 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed.
Vapours are heavier than air and spread along ground.
Use only in thoroughly ventilated areas.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Do not smoke - volatile.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.
Pay attention to anti-explosion rules.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

adhesive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL
8050-09-7	Rosin-based solder flux fume	-	0.05		TWA (8 h)	WEL
		-	0.15		STEL (15 min)	WEL

8.2. Exposure controls

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SOLUTION 12250 D

Revision date: 12.06.2019

Product code: 00156-0437

Page 5 of 10

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Splash protection:

Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance (wear duration) > 30 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Colourless
Odour:	Hydrocarbon-like

pH-Value: n.d.

Changes in the physical state

Melting point: n.d.

Initial boiling point and boiling range: 77 °C

Sublimation point: n.a.

Softening point: n.d.

Flash point: - 1 °C

Sustaining combustion: UN Test L.2

Flammability

Solid: n.a.

Gas: n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: 2,1 vol. %

Upper explosion limits: 11,5 vol. %

Ignition temperature: 460 °C

Auto-ignition temperature

Solid: n.a.

Test method

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

SOLUTION 12250 D

Revision date: 12.06.2019

Product code: 00156-0437

Page 6 of 10

Gas:	n.a.
Decomposition temperature:	n.d.
Oxidizing properties	
Not oxidising.	
Vapour pressure: (at 20 °C)	97 hPa
Density (at 15 °C):	< 1 g/cm ³
Bulk density:	n.a.
Water solubility: (at 20 °C)	Immiscible
Solubility in other solvents	
n.d.	
Partition coefficient:	n.d.
Viscosity / dynamic:	n.d.
Viscosity / kinematic: (at 40 °C)	< 20,5 mm ² /s
Flow time:	n.d.
Vapour density:	n.d.
Evaporation rate:	n.d.
Solvent separation test:	n.d.
Solvent content:	> 95 %

9.2. Other information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.
Vapour/air mixtures are explosive at intensive warming.
Heating can release vapours which can be ignited.

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.
No toxicological data available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SOLUTION 12250 D

Revision date: 12.06.2019

Product code: 00156-0437

Page 7 of 10

Irritation and corrosivity

- Causes skin irritation.
- Causes serious eye irritation.

Sensitising effects

- Contains Colophony. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

- Based on available data, the classification criteria are not met.

STOT-single exposure

- May cause drowsiness or dizziness. (Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes; Ethyl acetate)

STOT-repeated exposure

- Based on available data, the classification criteria are not met.

Aspiration hazard

- May be fatal if swallowed and enters airways.

Additional information on tests

- Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

- Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.
- Hazard of lung oedema.
- Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
- Contact with eyes may cause irritation.
- Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.
- Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

SECTION 12: Ecological information

12.1. Toxicity

- Ecological data are not available.
- Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

- Not readily biodegradable.

12.3. Bioaccumulative potential

- No data available

12.4. Mobility in soil

- No data available

12.5. Results of PBT and vPvB assessment

- According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

- Hazardous water pollutant.

Further information

- Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

- Where possible recycling is preferred to disposal.
- Can be incinerated, when in compliance with local regulations.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SOLUTION 12250 D

Revision date: 12.06.2019

Product code: 00156-0437

Page 8 of 10

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SOLUTION 12250 D

Revision date: 12.06.2019

Product code: 00156-0437

Page 9 of 10



Marine pollutant: Yes
Limited quantity: 5 L / 30 kg
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): > 95 %
Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS
Additional information: E2

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

SOLUTION 12250 D

Revision date: 12.06.2019

Product code: 00156-0437

Page 10 of 10

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Colophony. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)