

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP SOLVENT LIQUID BUFFER

Revision date: 04.09.2019

Product code: 00156-0008

Page 1 of 10

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

TIP TOP SOLVENT LIQUID BUFFER

##### Art.-No.

505 9685, 505 9702, 505 9719, 505 9740, 507 9706, 511 1190, 514 4870, 599 2200

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Cleaning agent

##### 1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG

Street: Gruber Strasse 65

Place: D-85586 Poing

Telephone: +49 (0) 8121 / 707 - 100

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

##### 1.4. Emergency telephone

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

##### number:

In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Toxic to aquatic life with long lasting effects.

##### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

Naphtha (petroleum)

Signal word: Danger

##### Pictograms:



##### Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP SOLVENT LIQUID BUFFER

Revision date: 04.09.2019

Product code: 00156-0008

Page 2 of 10

#### Precautionary statements

P261	Avoid breathing vapour.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P273	Avoid release to the environment.
P391	Collect spillage.

#### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.  
Vapours may form explosive mixture with air.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Preparation solved in petroleum spirit

##### Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
	Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 5% n-hexane]			> = 75 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, < 5% n-hexane]			<= 25 %
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			

Full text of H and EUH statements: see section 16.

##### Further Information

According to note P to the regulation (EC) no. 1272/2008, "Naphtha (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.  
Take away from danger area and lay down affected person.

##### After inhalation

Move to fresh air in case of accidental inhalation of vapours.  
If you feel unwell, seek medical advice.

##### After contact with skin

Wash off with soap and plenty of water.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP SOLVENT LIQUID BUFFER

Revision date: 04.09.2019

Product code: 00156-0008

Page 3 of 10

Consult a doctor if skin irritation persists.

#### **After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical treatment by eye specialist.

#### **After ingestion**

Do not induce vomiting.  
Summon a doctor immediately.  
Induce vomiting only upon the advice of a physician.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Causes skin irritation.  
May cause drowsiness or dizziness.  
May be fatal if swallowed and enters airways. Attention. Beware, danger of aspiration.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

##### **Unsuitable extinguishing media**

Full water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Fire may produce:  
carbon monoxide and carbon dioxide

#### **5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.  
Protective suit.

#### **Additional information**

Vapours are heavier than air and spread along ground.  
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.  
Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.  
Use only explosion-proof equipment.  
Avoid contact with skin, eyes and clothing.  
Ensure adequate ventilation.  
Use personal protective clothing.

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

#### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Shovel into suitable container for disposal.

#### **6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).  
Information for disposal see section 13.

### **SECTION 7: Handling and storage**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP SOLVENT LIQUID BUFFER

Revision date: 04.09.2019

Product code: 00156-0008

Page 4 of 10

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

- Keep container tightly closed.
- Vapours are heavier than air and spread along ground.
- Use only in thoroughly ventilated areas.
- Avoid contact with skin, eyes and clothing.

##### **Advice on protection against fire and explosion**

- Do not smoke - volatile.
- Keep away from heat and sources of ignition.
- Take precautionary measures against static discharges.
- Use only explosion-proof equipment.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

- Keep container tightly closed in a dry, cool and well-ventilated place.
- Pay attention to anti-explosion rules.

##### **Hints on joint storage**

- Incompatible with oxidizing agents.

##### **Further information on storage conditions**

- Keep away from food, drink and animal feeding stuffs.

#### **7.3. Specific end use(s)**

- Cleaning agent

### **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**

#### **8.2. Exposure controls**

##### **Appropriate engineering controls**

- Ensure adequate ventilation, especially in confined areas.

##### **Protective and hygiene measures**

- Do not inhale vapours.
- Wash hands before breaks and immediately after handling the product.
- When using do not eat, drink or smoke.
- Treat subsequently with skin cream.
- Remove and wash contaminated clothes before re-use.

##### **Eye/face protection**

- Tightly fitting goggles (EN 166).

##### **Hand protection**

- Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by [www.kcl.de](http://www.kcl.de).
- This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
- Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

##### **Skin protection**

- Solvent-resistant apron (EN 467).

##### **Respiratory protection**

- In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP SOLVENT LIQUID BUFFER**

Revision date: 04.09.2019

Product code: 00156-0008

Page 5 of 10

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: Liquid  
Colour: Colourless  
Odour: Hydrocarbon-like

**Test method**

pH-Value: n.a.

**Changes in the physical state**

Melting point: n.d.  
Initial boiling point and boiling range: 60 - 95 °C ASTM D1078  
Sublimation point: n.a.  
Softening point: n.d.  
Flash point: - 25 °C

**Flammability**

Solid: n.a.  
Gas: n.a.

**Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: 1,0 vol. %  
Upper explosion limits: 7,3 vol. %  
Ignition temperature: 413 °C

**Auto-ignition temperature**

Solid: n.a.  
Gas: n.a.

Decomposition temperature: n.d.

**Oxidizing properties**

Not oxidising.

Vapour pressure: 150 hPa  
(at 20 °C)Density (at 15 °C): 0,693 g/cm<sup>3</sup> DIN 51757

Bulk density: n.a.

Water solubility: 0,02 g/L  
(at 20 °C)

Partition coefficient: (n-octanol/water) Log Pow: 4 - 5,1

Viscosity / dynamic: 0,45 mPa·s

Viscosity / kinematic: < 20,5 mm<sup>2</sup>/s  
(at 40 °C)

Flow time: n.d.

Vapour density: n.d.

Evaporation rate: 7,6 ASTM D 3539

Solvent separation test: 0 %

Solvent content: 100 %

**9.2. Other information**

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP SOLVENT LIQUID BUFFER

Revision date: 04.09.2019

Product code: 00156-0008

Page 6 of 10

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

No decomposition if stored and applied as directed.

##### 10.2. Chemical stability

Stable under normal conditions.

##### 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

##### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.  
Vapour/air mixtures are explosive at intensive warming.  
Heating can release vapours which can be ignited.

##### 10.5. Incompatible materials

oxidizing agents

##### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide

#### SECTION 11: Toxicological information

##### 11.1. Information on toxicological effects

###### **Acute toxicity**

Based on available data, the classification criteria are not met.  
LD50/oral/rat: > 2000 mg/kg  
LD50/dermal/rabbit: > 2000 mg/kg  
LC50/inhalation/rat: > 20 mg/l

###### **Irritation and corrosivity**

Causes skin irritation.  
Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

###### **Sensitising effects**

Based on available data, the classification criteria are not met.

###### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

###### **STOT-single exposure**

May cause drowsiness or dizziness. (Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 5% n-hexane]; Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, < 5% n-hexane] )

###### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

###### **Aspiration hazard**

May be fatal if swallowed and enters airways.

###### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

###### **Practical experience**

###### **Other observations**

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.  
Hazard of lung oedema.  
Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.  
Contact with eyes may cause irritation.  
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP SOLVENT LIQUID BUFFER

Revision date: 04.09.2019

Product code: 00156-0008

Page 7 of 10

#### SECTION 12: Ecological information

##### 12.1. Toxicity

Naphtha (petroleum)  
EC50/Daphnia: 1 - 10 mg/l  
EC50/Algae: 10 - 100 mg/l  
Toxic to aquatic life with long lasting effects.

##### 12.2. Persistence and degradability

The product is readily biodegradable to OECD criteria.

##### 12.3. Bioaccumulative potential

No data available

##### 12.4. Mobility in soil

No data available

##### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

##### 12.6. Other adverse effects

Low hazard to waters.

##### **Further information**

Do not flush into surface water or sanitary sewer system.

#### SECTION 13: Disposal considerations

##### 13.1. Waste treatment methods

###### **Advice on disposal**

Where possible recycling is preferred to disposal.  
Can be incinerated, when in compliance with local regulations.

###### **Waste disposal number of waste from residues/unused products**

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08);  
waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent  
mixtures; hazardous waste

###### **Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.  
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken  
for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.

#### SECTION 14: Transport information

##### **Land transport (ADR/RID)**

<b><u>14.1. UN number:</u></b>	UN 1263
<b><u>14.2. UN proper shipping name:</u></b>	Paint related material
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	II
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP SOLVENT LIQUID BUFFER

Revision date: 04.09.2019

Product code: 00156-0008

Page 8 of 10

Excepted quantity: E2  
 Transport category: 2  
 Hazard No: 33  
 Tunnel restriction code: D/E

#### Inland waterways transport (ADN)

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint related material  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L / 30 kg  
 Excepted quantity: E2

#### Marine transport (IMDG)

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint related material (Naphtha (petroleum))  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Marine pollutant: Yes  
 Limited quantity: 5 L / 30 kg  
 Excepted quantity: E2  
 EmS: F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint related material  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

#### 14.5. Environmental hazards



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP SOLVENT LIQUID BUFFER

Revision date: 04.09.2019

Product code: 00156-0008

Page 9 of 10

ENVIRONMENTALLY HAZARDOUS: yes



#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

2004/42/EC (VOC):	95 - 100 %
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS

##### National regulatory information

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
--------------------------	--

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

### SECTION 16: Other information

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses  
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure  
IMDG = International Maritime Code for Dangerous Goods  
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization  
MARPOL = International Convention for the Prevention of Pollution from Ships  
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals  
CAS = Chemical Abstract Service  
EN = European norm  
ISO = International Organization for Standardization  
DIN = Deutsche Industrie Norm  
PBT = Persistent Bioaccumulative and Toxic  
vPvB = Very Persistent and very Bio-accumulative  
LD = Lethal dose  
LC = Lethal concentration  
EC = Effect concentration  
IC = Median immobilisation concentration or median inhibitory concentration

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP SOLVENT LIQUID BUFFER**

Revision date: 04.09.2019

Product code: 00156-0008

Page 10 of 10

H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*