

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE TC 5000

Revision date: 11.04.2017

Product code: 00359-1237

Page 2 of 10

Hazard statements

H226	Flammable liquid and vapour.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P273	Avoid release to the environment.

Special labelling of certain mixtures

EUH208	Contains Di(benzothiazol-2-yl) disulphide. May produce an allergic reaction.
--------	--

2.3. Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Preparation in xylene

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
1330-20-7	Xylene (mixed isomers)			< 80 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H312 H332 H315 H319 H335 H373 H304			
120-78-5	Di(benzothiazol-2-yl) disulphide			< 1 %
	204-424-9	613-135-00-0	01-2119489366-24	
	Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410 EUH031			
137-26-8	Thiram			< 0,1 %
	205-286-2	006-005-00-4	01-2119492301-45	
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H302 H332 H315 H319 H317 H373 H400 H410			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE TC 5000

Revision date: 11.04.2017

Product code: 00359-1237

Page 3 of 10

General information

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.
Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.
Treat subsequently with skin cream.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Summon a doctor immediately.
The decision whether to induce vomiting or not is to be taken by a physician.

4.2. Most important symptoms and effects, both acute and delayed

Harmful in contact with skin or if inhaled.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide (CO), carbon dioxide (CO₂) and sulphur oxides (SO_x)
Bromine compounds

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Vapours are heavier than air and spread along ground.
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE TC 5000

Revision date: 11.04.2017

Product code: 00359-1237

Page 4 of 10

In case of vapour formation use respirator.
Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.
Clean contaminated surface thoroughly.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal see section 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed.
Use only in area provided with appropriate exhaust ventilation.
In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

Advice on protection against fire and explosion

Keep product and empty container away from heat and sources of ignition.
Pay attention to anti-explosion rules.
Do not smoke.
Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep containers tightly closed in a cool, well-ventilated place.
Keep away from heat and sources of ignition.

Advice on storage compatibility

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

adhesive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE TC 5000

Revision date: 11.04.2017

Product code: 00359-1237

Page 5 of 10

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

8.2. Exposure controls**Appropriate engineering controls**

- Ensure adequate ventilation, especially in confined areas.
- Pay attention to explosion protection guidelines.

Protective and hygiene measures

- Do not inhale vapours.
- Avoid contact with eyes and skin.
- Wash hands before breaks and immediately after handling the product.
- When using do not eat, drink or smoke.
- Remove and wash contaminated clothes before re-use.

Eye/face protection

- Tightly fitting goggles (EN 166).
- Eye wash bottle with pure water (EN 15154).

Hand protection

- Protective gloves resistant to chemicals made off viton, minimum coat thickness 0,7 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
- Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

- Long sleeved clothing (EN 368).

Respiratory protection

- In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Black
Odour:	Hydrocarbon-like

Test method**Changes in the physical state**

Initial boiling point and boiling range:	137 - 142 °C (*)
Flash point:	24 °C (*)
Lower explosion limits:	1,0 vol. % (*)
Upper explosion limits:	7,0 vol. % (*)
Ignition temperature:	approx. 460 °C (*)
Vapour pressure: (at 20 °C)	8 hPa (*)
Density (at 20 °C):	0,91 g/cm ³
Water solubility:	Immiscible
Viscosity / dynamic:	approx. 2000 mPa·s



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE TC 5000

Revision date: 11.04.2017

Product code: 00359-1237

Page 6 of 10

Viscosity / kinematic: > 20,5 mm²/s
(at 40 °C)

Solvent content: < 80 %

9.2. Other information

(* Xylene (mixed isomers))

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapours may form explosive mixture with air.

An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide, carbon dioxide, sulphur oxides.
bromine compounds

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful in contact with skin or if inhaled.

No toxicological data available.

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Xylene (mixed isomers))

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Xylene (mixed isomers))

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Inhalation of vapours in high concentration can cause narcotic effects.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE TC 5000

Revision date: 11.04.2017

Product code: 00359-1237

Page 7 of 10

Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.
Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.
Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.
Packaging that cannot be cleaned should be disposed of like the product.
Empty containers should be taken for local recycling, recovery or waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1133
<u>14.2. UN proper shipping name:</u>	Adhesives
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	III
Hazard label:	3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE TC 5000

Revision date: 11.04.2017

Product code: 00359-1237

Page 8 of 10



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: No
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE TC 5000

Revision date: 11.04.2017

Product code: 00359-1237

Page 9 of 10

IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): < 80 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE TC 5000

Revision date: 11.04.2017

Product code: 00359-1237

Page 10 of 10

H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH031	Contact with acids liberates toxic gas.
EUH208	Contains Di(benzothiazol-2-yl) disulphide. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)