

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Asplit® CN Solution

Art.-No.

592 0020, 592 0021, 592 0022, 592 0023

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Mortar

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone

number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24
24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Acute toxicity: Acute Tox. 3

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1A

Germ cell mutagenicity: Muta. 2

Carcinogenicity: Carc. 1B

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Toxic if swallowed.

Harmful in contact with skin or if inhaled.

May cause respiratory irritation.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

May cause cancer.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard components for labelling

2-Furaldehyde

Phenol

formaldehyde

N-(3-(trimethoxysilyl)propyl)ethylenediamine

Signal word:

Danger

Pictograms:



Hazard statements

H301 Toxic if swallowed.

H312+H332 Harmful in contact with skin or if inhaled.

Asplit® CN Solution

Revision date: 15.06.2016

Revision No: 1,3

Product code: 00359-1166

| | |
|------|--|
| H335 | May cause respiratory irritation. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H341 | Suspected of causing genetic defects. |
| H350 | May cause cancer. |
| H412 | Harmful to aquatic life with long lasting effects. |

Precautionary statements

| | |
|-----------|--|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P260 | Do not breathe vapour. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. |
| P405 | Store locked up. |
| P273 | Avoid release to the environment. |

2.3. Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Mixture containing following substances with additives

Hazardous components

| CAS No | Chemical name | | | Quantity |
|-----------|--|--------------|------------------|----------|
| | EC No | Index No | REACH No | |
| | Classification according to Regulation (EC) No. 1272/2008 [CLP] | | | |
| 98-01-1 | 2-Furaldehyde | | | < 30 % |
| | 202-627-7 | 605-010-00-4 | 01-2119486861-27 | |
| | Carc. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H351 H301 H331 H312 H315 H319 H335 | | | |
| 108-95-2 | Phenol | | | < 10 % |
| | 203-632-7 | 604-001-00-2 | 01-2119471329-32 | |
| | Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, STOT RE 2, Aquatic Chronic 2; H341 H301 H311 H331 H314 H373 H411 | | | |
| 50-00-0 | formaldehyde | | | < 1 % |
| | 200-001-8 | 605-001-00-5 | 01-2119488953-20 | |
| | Carc. 1B, Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Skin Sens. 1A; H350 H341 H301 H311 H331 H314 H317 | | | |
| 1760-24-3 | N-(3-(trimethoxysilyl)propyl)ethylenediamine | | | < 1 % |
| | 217-164-6 | | 01-2119970215-39 | |
| | Eye Dam. 1, Skin Sens. 1; H318 H317 | | | |

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.
 In the event of persistent symptoms receive medical treatment.
 Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
 Seek medical treatment immediately.

After contact with skin

Wash off immediately with soap and plenty of water.
 Consult a doctor if skin irritation persists.



After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Consult (eye) doctor immediately.

After ingestion

Do not induce vomiting.
Summon a doctor immediately.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

May cause cancer.
Suspected of causing genetic defects.
Toxic if swallowed.
Harmful in contact with skin or if inhaled.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May cause respiratory irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.
Attention. Phenols in high amounts cause local anesthetic effects so that pain due to burns may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
Carbon monoxide and carbon dioxide
Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Vapours are heavier than air and spread along ground.
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Cool containers at risk with water spray jet.
Collect contaminated firefighting water separately, must not be discharged into the drains.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.
Ensure adequate ventilation.
Remove persons to safety.
Use personal protective clothing.
Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.
Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.



Asplit® CN Solution

Revision date: 15.06.2016

Revision No: 1,3

Product code: 00359-1166

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Use only in thoroughly ventilated areas.

Provide suitable extraction at the processing machines.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Take measures against electrostatically charging.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Advice on storage compatibility

Incompatible with acids.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Mortar

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|----------|--------------------------|-----|-------------------|-----------|---------------|--------|
| 98-01-1 | 2-Furaldehyde (furfural) | 2 | 8 | | TWA (8 h) | WEL |
| | | 5 | 20 | | STEL (15 min) | WEL |
| 50-00-0 | Formaldehyde | 2 | 2.5 | | TWA (8 h) | WEL |
| | | 2 | 2.5 | | STEL (15 min) | WEL |
| 108-95-2 | Phenol | 2 | 7.8 | | TWA (8 h) | WEL |
| | | 4 | 16 | | STEL (15 min) | WEL |

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Pay attention to explosion protection guidelines.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0,7 mm, permeation resistance approx. 480 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN



374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (EN 368).

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------|---------------|
| Physical state: | Liquid |
| Colour: | Dark brown |
| Odour: | Like phenoles |

Changes in the physical state

| | | |
|--|-------------------|-----------------|
| Initial boiling point and boiling range: | 100 - 200 °C | |
| Flash point: | 78 °C | DIN EN ISO 2719 |
| Lower explosion limits: | 2,1 vol. % | (*) |
| Upper explosion limits: | 19,3 vol. % | (*) |
| Ignition temperature: | 315 °C | (*) |
| Decomposition temperature: | > 110 °C | |
| Vapour pressure: | ~ 1,4 hPa | (*) |
| Density: | 1,221 g/cm³ | |
| Water solubility: (at 20 °C) | Partially soluble | |
| Viscosity / dynamic: (at 23 °C) | 125 - 165 mPa·s | ISO 3219 |

9.2. Other information

(*) Solvent

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with strong acids.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

Avoid temperatures above 25°C .

10.5. Incompatible materials

Strong acids.

10.6. Hazardous decomposition products

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity



Toxic if swallowed.

Harmful in contact with skin or if inhaled.

No toxicological data available.

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

May cause an allergic skin reaction. (formaldehyde), (N-(3-(trimethoxysilyl)propyl)ethylenediamine)

STOT-single exposure

May cause respiratory irritation. (2-Furaldehyde)

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (Phenol), (formaldehyde)

May cause cancer. (formaldehyde)

Reproductive toxicity: Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

Waste disposal number of waste from residues/unused products

080409


WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances
Classified as hazardous waste.

Contaminated packaging


Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.


SECTION 14: Transport information
Land transport (ADR/RID)

| | |
|--|--|
| 14.1. UN number: | UN 2927 |
| 14.2. UN proper shipping name: | TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (2-Furaldehyde, Phenol) |
| 14.3. Transport hazard class(es): | 6.1 |
| 14.4. Packing group: | II |
| Hazard label: | 6.1+8  |
| Classification code: | TC1 |
| Limited quantity: | 100 mL / 30 kg |
| Excepted quantity: | E4 |
| Transport category: | 2 |
| Hazard No: | 68 |
| Tunnel restriction code: | D/E |

Inland waterways transport (ADN)

| | |
|--|--|
| 14.1. UN number: | UN 2927 |
| 14.2. UN proper shipping name: | TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (2-Furaldehyde, Phenol) |
| 14.3. Transport hazard class(es): | 6.1 |
| 14.4. Packing group: | II |
| Hazard label: | 6.1+8  |
| Classification code: | TC1 |
| Limited quantity: | 100 mL / 30 kg |
| Excepted quantity: | E4 |

Marine transport (IMDG)

| | |
|--|--|
| 14.1. UN number: | UN 2927 |
| 14.2. UN proper shipping name: | TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (2-Furaldehyde, phenol) |
| 14.3. Transport hazard class(es): | 6.1 |
| 14.4. Packing group: | II |
| Hazard label: | 6.1+8  |
| Marine pollutant: | No |
| Limited quantity: | 100 mL / 30 kg |
| Excepted quantity: | E4 |
| EmS: | F-A, S-B |

Air transport (ICAO)

| | |
|--|--|
| 14.1. UN number: | UN 2927 |
| 14.2. UN proper shipping name: | TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (2-Furaldehyde, phenol, solution) |
| 14.3. Transport hazard class(es): | 6.1 |
| 14.4. Packing group: | II |
| Hazard label: | 6.1+8 |

Asplit® CN Solution

Revision date: 15.06.2016

Revision No: 1,3

Product code: 00359-1166



| | | |
|--|-------|------|
| Limited quantity Passenger: | 0.5 L | |
| Passenger LQ: | Y640 | |
| Excepted quantity: | E4 | |
| IATA-packing instructions - Passenger: | | 653 |
| IATA-max. quantity - Passenger: | | 1 L |
| IATA-packing instructions - Cargo: | | 660 |
| IATA-max. quantity - Cargo: | | 30 L |

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): < 30 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - water contaminating

Additional information

Consider Chemical prohibition regulation.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

- ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
- RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
- ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
- IMDG = International Maritime Code for Dangerous Goods
- IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
- MARPOL = International Convention for the Prevention of Pollution from Ships
- IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
- CAS = Chemical Abstract Service
- EN = European norm
- ISO = International Organization for Standardization
- DIN = Deutsche Industrie Norm
- PBT = Persistent Bioaccumulative and Toxic
- vPvB = Very Persistent and very Bio-accumulative

- LD = Lethal dose
- LC = Lethal concentration
- EC = Effect concentration
- IC = Median immobilisation concentration or median inhibitory concentration



Asplit® CN Solution

Revision date: 15.06.2016

Revision No: 1,3

Product code: 00359-1166

Relevant H and EUH statements (number and full text)

| | |
|-----------|--|
| H301 | Toxic if swallowed. |
| H311 | Toxic in contact with skin. |
| H312 | Harmful in contact with skin. |
| H312+H332 | Harmful in contact with skin or if inhaled. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H335 | May cause respiratory irritation. |
| H341 | Suspected of causing genetic defects. |
| H350 | May cause cancer. |
| H351 | Suspected of causing cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)