

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Asplit® LC Hardener

Art.-No.

592 0830

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hardener

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone

number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Flammable liquid: Flam. Liq. 3

Substance or mixture corrosive to metals: Met. Corr. 1

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Flammable liquid and vapour.

May be corrosive to metals.

Causes severe skin burns and eye damage.

May cause drowsiness or dizziness.

2.2. Label elements

Hazard components for labelling

Sulfophenolic acid

Propan-2-ol

Phosphoric acid

Signal word:

Danger

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Asplit® LC Hardener

Revision date: 02.06.2016

Revision No: 1,1

Product code: 00359-1208

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P406	Store in corrosive resistant container with a resistant inner liner.

2.3. Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Mixture containing following substances with additives

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
98-67-9	Sulfophenolic acid			< 65 %
	202-691-6		01-2119538813-35	
	Met. Corr. 1, Skin Corr. 1B; H290 H314			
67-63-0	Propan-2-ol			< 25 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
104-15-4	p-toluenesulphonic acid (containing a maximum of 5 % H ₂ SO ₄)			< 15 %
	203-180-0	016-030-00-2	01-2119538811-39	
	Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H315 H319 H335			
7664-38-2	Phosphoric acid			< 10 %
	231-633-2	015-011-00-6	01-2119485924-24	
	Met. Corr. 1, Skin Corr. 1B; H290 H314			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.
 In the event of persistent symptoms receive medical treatment.
 Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
 In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.
 Seek medical treatment immediately.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
 Consult (eye) doctor immediately.

After ingestion

Do not induce vomiting.
 Summon a doctor immediately.
 Rinse out mouth and give plenty of water to drink.
 Never give anything by mouth to an unconscious person.



Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage.

May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO₂), sulphur oxides (SO_x) and phosphorus oxides (PO_x).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Avoid contact with skin, eyes and clothing.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Do not use metal containers.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Provide appropriate ventilation and exhaust ventilation at the workplaces.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in original container.



Asplit® LC Hardener

Revision date: 02.06.2016

Revision No: 1,1

Product code: 00359-1208

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

Advice on storage compatibility

Incompatible with bases.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
7664-38-2	Orthophosphoric acid	-	1		TWA (8 h)	WEL
		-	2		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off viton , Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) approx. 60 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (EN 368).

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

Environmental exposure controls

Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Colourless
Odour:	characteristic
pH-Value:	n.d.



Changes in the physical state

Flash point:	approx. 41 °C
Lower explosion limits:	2,0 vol. %
Upper explosion limits:	12,0 vol. %
Ignition temperature:	approx. 350 °C
Vapour pressure:	43 hPa
(at 20 °C)	
Density:	approx. 1,18 g/cm ³
Water solubility:	Miscible
(at 20 °C)	
Viscosity / kinematic:	> 7 - < 20,5 mm ² /s
(at 40 °C)	
Solvent content:	< 25 %

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with alkalies.

10.4. Conditions to avoid

Heating can release vapours which can be ignited.

Vapours may form explosive mixture with air.

Gives off hydrogen by reaction with metals.

10.5. Incompatible materials

Bases.

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO₂), sulphur oxides (SO_x) and phosphorus oxides (PO_x).

Hydrogen, by reaction with metals.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Propan-2-ol)

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.



SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances
Classified as hazardous waste.

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN 2920

14.2. UN proper shipping name:

CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Sulfophenolic acid, Propan-2-ol)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8+3



Classification code:

CF1

Limited quantity:

1 L / 30 kg

Excepted quantity:

E2

Transport category:

2

Hazard No:

83

Tunnel restriction code:

D/E

Inland waterways transport (ADN)

14.1. UN number:

UN 2920

Asplit® LC Hardener

Revision date: 02.06.2016

Revision No: 1,1

Product code: 00359-1208

14.2. UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Sulfophenolic acid, Propan-2-ol)

14.3. Transport hazard class(es): 8

14.4. Packing group: II

Hazard label: 8+3



Classification code: CF1

Limited quantity: 1 L / 30 kg

Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 2920

14.2. UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Sulfophenolic acid, Propan-2-ol)

14.3. Transport hazard class(es): 8

14.4. Packing group: II

Hazard label: 8+3



Marine pollutant: No

Limited quantity: 1 L / 30 kg

Excepted quantity: E2

EmS: F-E, S-C

Air transport (ICAO)

14.1. UN number: UN 2920

14.2. UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Sulfophenolic acid, Propan-2-ol, mixture)

14.3. Transport hazard class(es): 8

14.4. Packing group: II

Hazard label: 8+3



Limited quantity Passenger: 0.5 L

Passenger LQ: Y840

Excepted quantity: E2

IATA-packing instructions - Passenger: 851

IATA-max. quantity - Passenger: 1 L

IATA-packing instructions - Cargo: 855

IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



EU regulatory information

2004/42/EC (VOC): < 25 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)