

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT OTR

Revision date: 18.05.2017

Product code: 00156-0359

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP CEMENT OTR

Art.-No.

515 9430, 515 9431, 515 9440

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesive

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG
Street: Gruber Strasse 65
Place: D-85586 Poing
Telephone: +49 (0) 8121 / 707 - 100
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24
24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:
Flammable liquid: Flam. Liq. 2
Serious eye damage/eye irritation: Eye Irrit. 2
Specific target organ toxicity - single exposure: STOT SE 3
Hazardous to the aquatic environment: Aquatic Chronic 2
Hazard Statements:
Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Ethyl acetate
Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT OTR

Revision date: 18.05.2017

Product code: 00156-0359

Page 2 of 10

P260	smoking.
P280	Do not breathe vapour.
P303+P361+P353	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P312	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P273	Call a POISON CENTER/doctor if you feel unwell.
	Avoid release to the environment.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Preparation with ethyl acetate

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
141-78-6	Ethyl acetate			< 65 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
92062-15-2	Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane [Solvent naphta (petroleum)]			< 25 %
	926-605-8		01-2119486291-36	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411			
14634-93-6	Zinc-bis (N-ethyl-N-phenyldithiocarbamate)			< 5 %
	238-677-1			
	Eye Irrit. 2, Aquatic Chronic 4; H319 H413			
5459-93-8	N-Cyclohexyl-N-ethylamine			< 1 %
	226-733-8		01-2119949285-29	
	Flam. Liq. 3, Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Aquatic Chronic 3; H226 H311 H302 H332 H314 H412			
1314-13-2	Zinc oxide			< 1 %
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			

Full text of H and EUH statements: see section 16.

Further Information

According to note P to the regulation (EC) no. 1272/2008, "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

SECTION 4: First aid measures**4.1. Description of first aid measures**



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT OTR

Revision date: 18.05.2017

Product code: 00156-0359

Page 3 of 10

General information

Remove contaminated soaked clothing immediately.
If you feel unwell, seek medical advice.
Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off with soap and plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.
Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Vapours are heavier than air and spread along ground.
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.
Use only explosion-proof equipment.
Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT OTR

Revision date: 18.05.2017

Product code: 00156-0359

Page 4 of 10

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Keep a good ventilation and air-exhaust at the place of work.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

Advice on storage compatibility

Incompatible with:

Oxidizing agents

Nitrous acid and other nitrosating agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

adhesive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL

8.2. Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT OTR

Revision date: 18.05.2017

Product code: 00156-0359

Page 5 of 10

When using do not eat, drink or smoke.
Treat subsequently with skin cream.
Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).
Eye wash bottle with pure water (EN 15154).

Hand protection

Splash protection:
Protective gloves resistant to chemicals made off natural-rubber latex, minimum coat thickness 0.6 mm, permeation resistance (wear duration) approx. 10 minutes, i.e. protective glove <Lapren 706> made by www.kcl.de.
Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance (wear duration) > 60 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Blue
Odour:	Ester-like

Test method**Changes in the physical state**

Flash point:	- 20 °C	DIN EN ISO 3679
Lower explosion limits:	2,1 vol. %	
Upper explosion limits:	11,5 vol. %	
Ignition temperature:	460 °C	
Vapour pressure: (at 20 °C)	100 hPa	
Density (at 20 °C):	0,88 g/cm ³	
Water solubility: (at 20 °C)	Immiscible	
Viscosity / dynamic: (at 20 °C)	4500 - 6500 mPa·s	
Viscosity / kinematic: (at 40 °C)	> 20,5 mm ² /s	
Flow time: (at 23 °C)	> 30 s	3 DIN EN ISO 2431
Solvent content:	< 85 %	

9.2. Other information

No data available.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT OTR

Revision date: 18.05.2017

Product code: 00156-0359

Page 6 of 10

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.
Vapour/air mixtures are explosive at intensive warming.
Heating can release vapours which can be ignited.

10.5. Incompatible materials

Nitrous acid and other nitrosating agents.
oxidizing agents

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide
An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.
No toxicological data available.

Irritation and corrosivity

Causes serious eye irritation.
Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Ethyl acetate; Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane [Solvent naphta (petroleum)])

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Effects of breathing high concentrations of vapour may include: Headache, dizziness, weakness, unconsciousness.
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT OTR

Revision date: 18.05.2017

Product code: 00156-0359

Page 7 of 10

Further information

An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane

LC50/EC50/EC50 : 1 - 10 mg/l

Zinc oxide

EC50/Ceriodaphnia dubia/48 h = 0,01 - 0,1 mg/l

EC50/Selenastrum capricornutum/72 h = 0,01 - 0,1 mg/l

N-Cyclohexyl-N-ethylamine

EC50/Daphnia magna/48 h = 10 - 100 mg/l

ErC50/Desmodesmus subspicatus/72 h = 10 - 100 mg/l

Ethyl acetate

LC50/EC50/EC50 : > 100 mg/l

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT OTR

Revision date: 18.05.2017

Product code: 00156-0359

Page 8 of 10

Land transport (ADR/RID)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives (Solvent naphtha (petroleum))
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Marine pollutant: Yes
Limited quantity: 5 L / 30 kg
Excepted quantity: E2
EmS: F-E, S-D

Other applicable information (marine transport)

Segregation group: -

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT OTR

Revision date: 18.05.2017

Product code: 00156-0359

Page 9 of 10

Hazard label:

3



Limited quantity Passenger:

1 L

Passenger LQ:

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger:

353

IATA-max. quantity - Passenger:

5 L

IATA-packing instructions - Cargo:

364

IATA-max. quantity - Cargo:

60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane [Solvent naphta (petroleum)]

2004/42/EC (VOC):

80 - 85 %

National regulatory information

Employment restrictions:

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D):

2 - water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT OTR

Revision date: 18.05.2017

Product code: 00156-0359

Page 10 of 10

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)