

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

TIP TOP COROFLAKE 200 A

#### Art.-No.

590 0693, 590 0703, 590 0710, 590 1770, 590 1780, 590 1820, 590 1830

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Coating material

### 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Responsible for the safety data sheet: sds@gbk-ingelheim.de

### 1.4. Emergency telephone

#### number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24  
24

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Indications of danger: Xi - Irritant, N - Dangerous for the environment

R phrases:

Irritating to skin.

May cause sensitisation by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### GHS classification

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Respiratory/skin sensitization: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes skin irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Hazardous components which must be listed on the label

Reaction product: bisphenol-F-epichlorine hydrine resins with average molecular weight <= 700

Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

1,6-bis(2,3-epoxypropoxy)hexane

Signal word:

Warning

Pictograms:

GHS07-GHS09



#### Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.



**TIP TOP COROFLAKE 200 A**

00359-1018

**Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P273 Avoid release to the environment.

**Special labelling of certain mixtures**

EUH205 Contains epoxy constituents. May produce an allergic reaction.

**2.3. Other hazards**

Not known.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Epoxy resin formulation, contains solvents

**Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
500-006-8	Reaction product: bisphenol-F-epichlorine hydrine resins with average molecular weight <= 700	< 75 %
28064-14-4	Xi - Irritant, N - Dangerous for the environment R38-43-51-53	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411	
271-846-8	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	< 10 %
68609-97-2	Xi - Irritant R38-43	
603-103-00-4	Skin Irrit. 2, Skin Sens. 1; H315 H317	
01-2119485289-22		
500-033-5	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	< 5 %
25068-38-6	Xi - Irritant, N - Dangerous for the environment R36/38-43-51-53	
603-074-00-8	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411	
01-2119456619-26		
240-260-4	1,6-bis(2,3-epoxypropoxy)hexane	< 1 %
16096-31-4	Xi - Irritant R36/38-43-52-53	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412	

Full text of R-, H- and EUH-phrases: see section 16.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

Remove contaminated soaked clothing immediately.  
 In the event of persistent symptoms receive medical treatment.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours or decomposition products.  
 In the event of symptoms refer for medical treatment.

**After contact with skin**

Wash off immediately with soap and plenty of water.  
 Consult a doctor if skin irritation persists.

**After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
 Seek medical treatment by eye specialist.

#### **After ingestion**

Induce vomiting only upon the advice of a physician.  
Immediately give plenty of water (if possible charcoal slurry).  
Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Causes skin irritation.  
May cause an allergic skin reaction.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

---

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

##### **Unsuitable extinguishing media**

Full water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Fire may produce:  
Carbon monoxide and carbon dioxide

#### **5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.  
Protective suit.

#### **Additional information**

Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.  
Ensure adequate ventilation.  
Use personal protective clothing.

#### **6.2. Environmental precautions**

Clean contaminated surface thoroughly.  
Do not discharge into the drains/surface waters/ground water.

#### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Shovel into suitable container for disposal.

#### **6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).  
Information for disposal see section 13.

---

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Keep container tightly closed.  
Use only in thoroughly ventilated areas.  
Avoid contact with skin, eyes and clothing.

##### **Advice on protection against fire and explosion**

No special protective measures against fire required.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.



Protect against direct sun radiation.

**Advice on storage compatibility**

Incompatible with:

Oxidizing agents, Amines, Acids and bases.

**Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

**7.3. Specific end use(s)**

Coating material

---

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**8.2. Exposure controls**

**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Protective and hygiene measures**

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

**Eye/face protection**

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

**Hand protection**

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

**Skin protection**

Long sleeved clothing (EN 368).

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 141).

---

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Viscous liquid
Colour:	Various
Odour:	Aromatic
Flash point:	> 100 °C
Lower explosion limits:	n.d.
Upper explosion limits:	
Density (at 20 °C):	1,17 - 1,21 g/cm <sup>3</sup>
Water solubility: (at 20 °C)	Immiscible
Ignition temperature:	n.d.
Viscosity / dynamic: (at 25 °C)	10000 - 18000 mPa·s
Viscosity / kinematic: (at 20 °C)	> 20,5 mm <sup>2</sup> /s

Flow time: > 40 s  
(at 25 °C)

6 DIN/ISO 2431

### **9.2. Other information**

No data available.

---

## **SECTION 10: Stability and reactivity**

### **10.1. Reactivity**

No decomposition if stored and applied as directed.

### **10.2. Chemical stability**

Stable under normal conditions.

### **10.3. Possibility of hazardous reactions**

Reactions with acids, alkalies and oxidizing agents  
Reactions with amines.

### **10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.  
Protect against direct sun radiation.

### **10.5. Incompatible materials**

Oxidizing agents, Amines, Acids and bases.

### **10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide.  
Phenol

---

## **SECTION 11: Toxicological information**

### **11.1. Information on toxicological effects**

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

LD50/oral/rat: > 15000 mg/kg

LD50/dermal/rabbit: > 23000 mg/kg

#### **Irritation and corrosivity**

Causes skin irritation.

Eye irritation: Not classified.

#### **Sensitising effects**

May cause an allergic skin reaction. (Reaction product: bisphenol-F-epichlorine hydrine resins with average molecular weight <= 700), (Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. ), (Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) ), (1,6-bis(2,3-epoxypropoxy)hexane)

#### **STOT-single exposure**

Based on available data, the classification criteria are not met.

#### **Severe effects after repeated or prolonged exposure**

Based on available data, the classification criteria are not met.

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

---

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

LC50/Oncorhynchus mykiss/96 h = 2 mg/l

EC50/Daphnia magna/48 h = 1,8 mg/l  
ErC50/Scenedesmus capricornutum/72 h = 11 mg/l

**12.2. Persistence and degradability**

Not readily biodegradable.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

**12.6. Other adverse effects**

Hazardous water pollutant.

**Further information**

Do not flush into surface water or sanitary sewer system.

---

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Advice on disposal**

Can be incinerated, when in compliance with local regulations.  
Where possible recycling is preferred to disposal.

**Waste disposal number of waste from residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances  
Classified as hazardous waste.

**Contaminated packaging**

Contaminated packagings are to be treated like the product itself.  
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.

---

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

<b><u>14.1. UN number:</u></b>	UN3082
<b><u>14.2. UN proper shipping name:</u></b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
<b><u>14.3. Transport hazard class(es):</u></b>	9
<b><u>14.4. Packing group:</u></b>	III
Hazard label:	9



Classification code:	M6
Limited quantity:	5 L / 30 kg
Transport category:	3
Hazard No:	90
Tunnel restriction code:	E

**Inland waterways transport (ADN)**

<b><u>14.1. UN number:</u></b>	UN3082
<b><u>14.2. UN proper shipping name:</u></b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)

**14.3. Transport hazard class(es):** 9

**14.4. Packing group:** III

Hazard label: 9



Classification code: M6

Limited quantity: 5 L / 30 kg

**Marine transport (IMDG)**

**14.1. UN number:** UN3082

**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Epoxy resin)

**14.3. Transport hazard class(es):** 9

**14.4. Packing group:** III

Hazard label: 9



Marine pollutant: Yes

Limited quantity: 5 L / 30 kg

EmS: F-A, S-F

**Air transport (ICAO)**

**14.1. UN number:** UN3082

**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Epoxy resin)

**14.3. Transport hazard class(es):** 9

**14.4. Packing group:** III

Hazard label: 9



Limited quantity Passenger: Y964 / 30 kg G

IATA-packing instructions - Passenger: 964

IATA-max. quantity - Passenger: 450 L

IATA-packing instructions - Cargo: 964

IATA-max. quantity - Cargo: 450 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: yes



**14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

The transport takes place only in approved and appropriate packaging.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

1999/13/EC (VOC): 0 %



### National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

### Additional information

Chemical prohibition regulation consider.

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

---

## SECTION 16: Other information

### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

### Relevant R-phrases (Number and full text)

36/38 Irritating to eyes and skin.

38 Irritating to skin.

43 May cause sensitisation by skin contact.

51 Toxic to aquatic organisms.

52 Harmful to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

### Relevant H- and EUH-phrases (Number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

### Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*