REMATIP TOP AG

#### TIP TOP RCF INNERLINER SEALER

Revision date: 26.11.2015 Revision No: 2,1

Product code: 00156-0391



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

TIP TOP RCF INNERLINER SEALER

**Art.-No.** 515 9090

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Tyre sealing material

### 1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG
Street: Gruber Strasse 63
Place: D-85586 Poing
Telephone: +49 (0) 8121 / 707 - 0

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

**1.4. Emergency telephone** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture according to 1272/2008/EC

This mixture is not classified as hazardous according to Regulation (EC) No. 1272/2008.

## 2.2. Label elements

# Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

#### 2.3. Other hazards

Not known.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

## **Chemical characterization**

Aqueous solution

### **Hazardous components**

CAS No	Chemical name						
	EC No	Index No	REACH No				
	Classification according to Regulation (EC) No. 1272/2008 [CLP]						
107-21-1	Ethane-1,2-diol						
	203-473-3	603-027-00-1	01-2119456816-28				
	Acute Tox. 4, STOT RE 2; H302 H373						

Full text of H and EUH statements: see section 16.

### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### **General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

### After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

#### After contact with skin

Wash off with soap and plenty of water.

REMATIP TOP AG

#### TIP TOP RCF INNERLINER SEALER

Revision date: 26.11.2015 Revision No: 2,1

Product code: 00156-0391



Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If eye irritation persists, consult a specialist.

### After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Call a physician immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

Inhalation of vapours may cause mild irritation to the mucous membrane.

Repeated or prolonged exposure may cause irritation of eyes and skin.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

## Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.

Foam, carbon dioxide (CO2), dry chemical, water-spray.

Sand

### Unsuitable extinguishing media

Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide and carbon dioxide

### 5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

#### Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective clothing.

## 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

# 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

## **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

## Advice on safe handling

Keep container tightly closed.

Avoid contact with the skin and the eyes.

### Advice on protection against fire and explosion

No special protective measures against fire required.

REMATIP TOP AG

#### TIP TOP RCF INNERLINER SEALER

Revision date: 26.11.2015 Revision No: 2,1

Product code: 00156-0391



#### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

### Advice on storage compatibility

Incompatible with oxidizing agents.

### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Tyre sealing material

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	WEL
		40	104		STEL (15 min)	WEL
57-55-6	Propane-1,2-diol, particulates	-	10		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

### 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

### Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and at the end of workday.

When using do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

### Eye/face protection

Safety goggles with side protection (EN 166).

## **Hand protection**

Protective gloves resistant to chemicals made off natural-rubber latex, minimum coat thickness 0.6 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Lapren 706> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

### Skin protection

Long sleeved clothing (EN 368).

#### Respiratory protection

No personal respiratory protective equipment normally required.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Black
Odour: Soft

pH-Value (at 20 °C): 8,1

REMATIP TOP AG

#### TIP TOP RCF INNERLINER SEALER

Revision date: 26.11.2015 Revision No: 2,1

Product code: 00156-0391



Changes in the physical state

Melting point:  $-5\,^{\circ}\mathrm{C}$  Flash point: n.a. Lower explosion limits: n.d.

Upper explosion limits:

Ignition temperature: n.d.

Density (at 20 °C): 1,0 g/cm³

Water solubility: Miscible

(at 20 °C)

Viscosity / dynamic: 24000 - 26000 mPa·s

(at 25 °C)

Flow time: 50 s 3 DIN EN ISO 2431

(at 23 °C)

## 9.2. Other information

No data available.

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No decomposition if stored and applied as directed.

### 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

## 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat. Heating can release vapours which can be ignited.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

### **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

## **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

Ethane-1,2-diol

LD50/oral/rat: 5840 mg/kg LD50/dermal/rabbit: 9530 mg/kg LC50/inhalation/rat: 50100 mg/m³/8 h LDLo/oral/Human: 398 mg/kg

## Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

# Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

REMATIP TOP AG

#### TIP TOP RCF INNERLINER SEALER

Revision date: 26.11.2015 Revision No: 2,1

Product code: 00156-0391



#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

## **Practical experience**

#### Other observations

Inhalation of vapours may cause mild irritation to the mucous membrane.

Repeated or prolonged exposure may cause irritation of eyes and skin.

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Ecological data are not available.

Ethane-1,2-diol

LC50/Oncorhynchus mykiss/96 h = 40761 mg/l

EC50/Daphnia magna/48 h = 41100 mg/l

### 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

No data available.

### 12.6. Other adverse effects

Low hazard to waters.

## **Further information**

Ecological injuries are not known or expected under normal use.

Do not flush into surface water or sanitary sewer system.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

### Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS

(PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and

sealants containing organic solvents or other hazardous substances

Classified as hazardous waste.

### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

## **SECTION 14: Transport information**

### Land transport (ADR/RID); Marine transport (IMDG); Air transport (ICAO); Inland waterways transport (ADN):

### 14.1. UN number:

No hazardous material as defined by the transport regulations.

## 14.2. UN proper shipping name:

No hazardous material as defined by the transport regulations.

### 14.3. Transport hazard class(es):

No hazardous material as defined by the transport regulations.

REMATIP TOP AG

#### TIP TOP RCF INNERLINER SEALER

Revision date: 26.11.2015 Revision No: 2,1

Product code: 00156-0391



#### 14.4. Packing group:

No hazardous material as defined by the transport regulations.

### 14.5. Environmental hazards

No hazardous material as defined by the transport regulations.

#### 14.6. Special precautions for user

No hazardous material as defined by the transport regulations.

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No hazardous material as defined by the transport regulations.

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

2004/42/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

#### **SECTION 16: Other information**

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

## Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

EUH210 Safety data sheet available on request.

#### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

REMATIP TOP AG

## **TIP TOP RCF INNERLINER SEALER**

Revision date: 26.11.2015 Revision No: 2,1

Product code: 00156-0391



(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)