TIP TOP Oberflaechenschutz Elbe GmbH

#### **TIP TOP REMACOAT A-80 POLY**

Revision date: 24.06.2015 Revision No: 1,1

Product code: 00359-1091



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TIP TOP REMACOAT A-80 POLY

Art.-No.

590 2921, 590 2922, 590 2940, 590 2952, 590 2960

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Coating system for protection against wear and corrosion

#### 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg
Telephone: +49(0)3491/635-50
Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

**1.4. Emergency telephone** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

#### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - repeated exposure: STOT RE 2 Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements: Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause damage to organs through prolonged or repeated exposure.

Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

# Hazardous components which must be listed on the label

Glyceryl poly(oxypropylene) triamine

Polyoxypropylene diamine Diethylmethylbenzenediamine

Signal word: Danger

Pictograms:



# **Hazard statements**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

TIP TOP Oberflaechenschutz Elbe GmbH

#### **TIP TOP REMACOAT A-80 POLY**

Revision date: 24.06.2015 Revision No: 1,1

Product code: 00359-1091



P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.

P405 Store locked up.

P273 Avoid release to the environment.

# 2.3. Other hazards

Not known.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

## **Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulati	on (EC) No. 1272/2008 [CLP]	•	
64852-22-8	Glyceryl poly(oxypropylene) triamine			< 40 %
	Skin Irrit. 2, Eye Dam. 1, Aquatic C			
9046-10-0	Polyoxypropylene diamine			< 30 %
	Acute Tox. 4, Skin Corr. 1B, Aquati			
68479-98-1	Diethylmethylbenzenediamine			< 20 %
	270-877-4	612-130-00-0	01-2119486805-25	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2, STOT RE 2, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1; H302 H312 H319 H373 H400 H410			
106246-33-7	4-4'-methylenebis(3-chloro-2,6- diethylaniline)			< 15 %
	402-130-7			

Full text of H and EUH phrases: see section 16.

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

Consult a physician.

Take away from danger area and lay down affected person.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

In the event of symptoms refer for medical treatment.

# After contact with skin

In case of contact with skin wash off immediately with plenty of water.

Consult a doctor if skin irritation persists.

# After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Summon a doctor immediately.

# After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Induce vomiting only upon the advice of a physician.

Summon a doctor immediately.

# 4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause damage to organs through prolonged or repeated exposure.

TIP TOP Oberflaechenschutz Elbe GmbH

#### **TIP TOP REMACOAT A-80 POLY**

Revision date: 24.06.2015 Product code: 00359-1091 Revision No: 1.1



#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

## Unsuitable extinguishing media

Full water jet.

# 5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

Chlorine compounds.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

# **Additional information**

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

#### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

# 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

## 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

# Advice on safe handling

Keep container tightly closed.

Avoid contact with the skin and the eyes.

Do not breathe aerosol

Use only in thoroughly ventilated areas.

# Advice on protection against fire and explosion

No special protective measures against fire required.

## 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

## Advice on storage compatibility

Incompatible with acids.

## Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

## 7.3. Specific end use(s)

Coating system for protection against wear and corrosion

TIP TOP Oberflaechenschutz Elbe GmbH

#### **TIP TOP REMACOAT A-80 POLY**

Revision date: 24.06.2015 Revision No: 1,1

Product code: 00359-1091



# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

## 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

## Protective and hygiene measures

Avoid contact with eves and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

Do not inhale aerosols

## Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

#### Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

#### Skin protection

Long sleeved clothing (EN 368).

# Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Viscous liquid
Colour: Various
Odour: Amine like

# Changes in the physical state

Flash point: > 100 °C
Lower explosion limits: n.d.
Ignition temperature: n.d.

Density (at 25 °C): 1,02 - 1,04 g/cm³ Water solubility: Immiscible

(at 20 °C)

Viscosity / dynamic: 1350 - 1600 mPa·s

(at 25 °C)

# 9.2. Other information

No data available.

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

No decomposition if stored and applied as directed.

# 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Reactions with strong acids.

TIP TOP Oberflaechenschutz Elbe GmbH

#### **TIP TOP REMACOAT A-80 POLY**

Revision date: 24.06.2015

Product code: 00359-1091



#### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

#### 10.5. Incompatible materials

Acids.

## 10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

Revision No: 1.1

Chlorine compounds.

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

#### **Acute toxicity**

Harmful if swallowed.

No toxicological data available.

ATEmix/oral: approx. 1200 mg/kg [Harmful if swallowed.]

ATEmix/dermal: > 2000 mg/kg ATEmix/inhalation: > 20 mg/l

## Irritation and corrosivity

Causes severe skin burns and eye damage.

## Sensitising effects

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

## Severe effects after repeated or prolonged exposure

May cause damage to organs through prolonged or repeated exposure.

(Diethylmethylbenzenediamine)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

# Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

## Practical experience

## Other observations

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Methaemoglobinaemia possible after skin contact.

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

# 12.2. Persistence and degradability

Not readily biodegradable.

# 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

# 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

## 12.6. Other adverse effects

Hazardous water pollutant.

TIP TOP Oberflaechenschutz Elbe GmbH

#### **TIP TOP REMACOAT A-80 POLY**

Revision date: 24.06.2015 Revision No: 1,1

Product code: 00359-1091



#### **Further information**

Do not flush into surface water or sanitary sewer system.

#### **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

#### Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

## Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS

(PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and

sealants containing organic solvents or other dangerous substances

Classified as hazardous waste.

# Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be

taken for reuse.

# **SECTION 14: Transport information**

Land transport (ADR/RID)

**14.1. UN number:** UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Classification code: C7

Limited quantity: 5 L / 30 kg

Excepted quantity: E1
Transport category: 3
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

**14.1. UN number:** UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 8



Classification code: C7
Limited quantity: 5 L / 30 kg
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine,

diethylmethylbenzenediamine)

TIP TOP Oberflaechenschutz Elbe GmbH

#### **TIP TOP REMACOAT A-80 POLY**

Revision date: 24.06.2015 Revision No: 1,1

Product code: 00359-1091



14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 8



8

Marine pollutant: Yes
Limited quantity: 5 L / 30 kg

Excepted quantity: E1

EmS: F-A, S-B

Air transport (ICAO)

**14.1. UN number:** UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3 A803

1 L

Y841

Excepted quantity:

E1

IATA-packing instructions - Passenger:852IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:856IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



# 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** regulatory information

2004/42/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment

restrictions for child bearing mothers and nursing.

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## **SECTION 16: Other information**

Print date: 24.06.2015 GB - EN Page 7 of 8

TIP TOP Oberflaechenschutz Elbe GmbH

#### **TIP TOP REMACOAT A-80 POLY**

Revision date: 24.06.2015 Revision No: 1,1

Product code: 00359-1091



# Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

FC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

# Relevant H- and EUH-phrases (Number and full text)

Relevant n- and con-phrases (Number and full text)		
H302	Harmful if swallowed.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

#### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)