TIP TOP Oberflaechenschutz Elbe GmbH

**REMAFIX 111 Comp. B** 

Revision date: 17.10.2016 Revision No: 1,1

Product code: 00359-1277



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

REMAFIX 111 Comp. B

Art.-No.

525 1220, 525 1240

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Leveling compound

### 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg
Telephone: +49(0)3491/635-50
Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@qbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

**Hazard Statements:** 

Causes severe skin burns and eye damage.

Causes serious eye damage. May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

# 2.2. Label elements

### Hazard components for labelling

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

 $2,\!4,\!6\text{-tris} (dimethylaminomethyl) phenol$ 

Xylylenediamine

Fatty acids, C18 unsaturated, trimers, reaction products with triethylenetetramine

Signal word: Danger

Pictograms:



# **Hazard statements**

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

TIP TOP Oberflaechenschutz Elbe GmbH

### **REMAFIX 111 Comp. B**

Revision date: 17.10.2016 Product code: 00359-1277 Revision No: 1,1



P310

P273

Immediately call a POISON CENTER/doctor. Avoid release to the environment.

2.3. Other hazards

Not known.

# **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

### **Chemical characterization**

Mixture containing following substances with additives

### **Hazardous components**

CAS No	Chemical name	Quantity				
	EC No	Index No	REACH No			
	Classification according to Regulat					
100-51-6	Benzyl alcohol	< 15 %				
	202-859-9	603-057-00-5	01-2119492630-38			
	Acute Tox. 4, Acute Tox. 4; H302 H					
38294-64-3	4,4'-Isopropylidenediphenol, oligon reaction products with 3-aminomet	< 15 %				
	500-101-4		01-2119965165-33			
	Skin Corr. 1B, Eye Dam. 1, Skin So					
90-72-2	2,4,6-tris(dimethylaminomethyl)phe	< 5 %				
	202-013-9	603-069-00-0	01-2119560597-27			
	Acute Tox. 4, Skin Corr. 1C, Eye D					
1477-55-0	Xylylenediamine	< 5 %				
	216-032-5		01-2119480150-50			
	Acute Tox. 4, Acute Tox. 4, Skin Co H332 H314 H318 H317 H412 EUH					
69-72-7	Salicylic acid	< 5 %				
	200-712-3		01-2119486984-17			
	Acute Tox. 4, Eye Dam. 1; H302 H					
162627-18-1	Fatty acids, C18 unsaturated, trime	< 5 %				
	605-297-6					
	Skin Sens. 1B, Aquatic Acute 1, Ac					
108-65-6	2-Methoxy-1-methylethyl acetate	< 5 %				
	203-603-9	607-195-00-7	01-2119475791-29			
	Flam. Liq. 3; H226					

Full text of H and EUH statements: see section 16.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

Call a physician immediately.

## After inhalation

Move to fresh air in case of accidental inhalation of vapours.

If patient is not breathing, apply artificial respiration. In case of breathing difficulties give oxygen.

In the event of symptoms refer for medical treatment.

## After contact with skin

In case of contact with skin wash off immediately with plenty of water.

Seek medical treatment immediately.

## After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

TIP TOP Oberflaechenschutz Elbe GmbH

#### **REMAFIX 111 Comp. B**

Revision date: 17.10.2016 Product code: 00359-1277 Revision No: 1,1



Remove contact lens.

Seek medical treatment by eye specialist.

### After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

Attention. Beware, danger of aspiration.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eve damage.

May cause an allergic skin reaction.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

## Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

### **Additional information**

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Clean contaminated surface thoroughly.

## 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

# Advice on safe handling

Keep container tightly closed.

Handle and open container with care.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

# Advice on protection against fire and explosion

No special protective measures against fire required.

TIP TOP Oberflaechenschutz Elbe GmbH

**REMAFIX 111 Comp. B** 

Revision date: 17.10.2016 Product code: 00359-1277 Revision No: 1,1



### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Do not use zinc, aluminium or copper containers.

### Advice on storage compatibility

Incompatible with:

oxidizing agents, Amines, Acids and bases.

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Leveling compound

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
1344-28-1	Aluminium oxides, inhalable dust	-	10		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
7727-43-7	Barium sulphate, respirable dust	-	4		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
		1	•			

## 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

# Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

#### Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

# **Hand protection**

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

## Skin protection

Long sleeved clothing (EN 368).

## Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

TIP TOP Oberflaechenschutz Elbe GmbH

# **REMAFIX 111 Comp. B**

Revision date: 17.10.2016 Product code: 00359-1277 Revision No: 1,1



### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: pasty Colour: White

Odour: characteristic

Changes in the physical state

Flash point: > 100 °C
Lower explosion limits: n.d.

Upper explosion limits:

Ignition temperature: n.d.

Density (at 20 °C): 1,94 g/cm³

Water solubility: Immiscible

(at 20 °C)

Viscosity / dynamic: pasty

### 9.2. Other information

No data available.

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No decomposition if stored and applied as directed.

#### 10.2. Chemical stability

Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Protect against direct sun radiation.

### 10.5. Incompatible materials

oxidizing agents, Amines, Acids and bases.

# 10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

Ammonia

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

# **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

## Irritation and corrosivity

Causes severe skin burns and eye damage.

#### Sensitising effects

May cause an allergic skin reaction. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine); (2,4,6-tris(dimethylaminomethyl)phenol); (Xylylenediamine); (Fatty acids, C18 unsaturated, trimers, reaction products with triethylenetetramine)

## STOT-single exposure

Based on available data, the classification criteria are not met.

### Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

TIP TOP Oberflaechenschutz Elbe GmbH

**REMAFIX 111 Comp. B** 

Revision date: 17.10.2016 Revision No: 1,1

Product code: 00359-1277



Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

## 12.2. Persistence and degradability

Not readily biodegradable.

### 12.3. Bioaccumulative potential

No data available.

# 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

#### 12.6. Other adverse effects

Hazardous water pollutant.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

## Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

### Waste disposal number of waste from residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances

Classified as hazardous waste.

#### Contaminated packaging

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

## **SECTION 14: Transport information**

## Land transport (ADR/RID)

**14.1. UN number:** UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol,

oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction

products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 8

TIP TOP Oberflaechenschutz Elbe GmbH

**REMAFIX 111 Comp. B** 

Revision date: 17.10.2016 Revision No: 1,1

Product code: 00359-1277





Classification code: C7

Limited quantity: 5 L / 30 kg

Excepted quantity: E1
Transport category: 3
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol,

oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction

products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 8



8

Classification code: C7

Limited quantity: 5 L / 30 kg

Excepted quantity: E1

Marine transport (IMDG)

**14.1. UN number:** UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol,

oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction

products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine)

14.3. Transport hazard class(es): 8

14.4. Packing group:

Hazard label: 8



Marine pollutant:

Limited quantity: 5 L / 30 kg

Excepted quantity: E1

EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 2735

**14.2. UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol,

oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction

products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 8



Limited quantity Passenger:

Passenger LQ: Y841
Excepted quantity: E1

TIP TOP Oberflaechenschutz Elbe GmbH

**REMAFIX 111 Comp. B** 

Revision date: 17.10.2016 Revision No: 1,1

Product code: 00359-1277



IATA-packing instructions - Passenger:852IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:856IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

# 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** regulatory information

2004/42/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

#### **SECTION 16: Other information**

## Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

TIP TOP Oberflaechenschutz Elbe GmbH

**REMAFIX 111 Comp. B** 

Revision date: 17.10.2016 Revision No: 1,1

Product code: 00359-1277



EUH071 Corrosive to the respiratory tract.

#### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)