

according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX S H3

Revision date: 08.06.2017

Product code: 00359-1085

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP REMAFIX S H3

Art.-No.

525 2891

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hardener

1.3. Details of the supplier of the safety data sheet

Company name:	TIP TOP Oberflaechenschutz El	lbe GmbH
Street:	Heuweg 4	
Place:	D-06886 Wittenberg	
Telephone:	+49(0)3491/635-50	Telefax: +49(0)3491/635-552
Responsible Department:	Responsible for the safety data	sheet: sds@gbk-ingelheim.de
1.4. Emergency telephone number:		32 - 84463, GBK GmbH (24h - 7d/w - 365d/a) t - 0845 4647; Scotland: NHS 24 - 08454 24 24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Acute toxicity: Acute Tox. 4 Skin corrosion/irritation: Skin Irrit. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Resp. Sens. 1 Respiratory or skin sensitisation: Skin Sens. 1 Carcinogenicity: Carc. 2 Specific target organ toxicity - single exposure: STOT SE 3 Specific target organ toxicity - repeated exposure: STOT RE 2 Hazard Statements: Harmful if inhaled. Causes skin irritation. Causes serious eve irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled . May cause an allergic skin reaction. Suspected of causing cancer. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Diphenylmethanediisocyanate, isomers and homologues Diphenylmethane-4,4'-diisocyanate Diphenylmethane-2,4'-diisocyanate Diphenylmethane-2,2'-diisocyanate

Danger

Signal word:

Revision No: 1,4



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX S H3

Revision date: 08.06.2017

Product code: 00359-1085

Page 2 of 10





Hazard statements

H332 Harmful if inhaled.	
H315 Causes skin irritation.	
H319 Causes serious eye irritation.	
H334 May cause allergy or asthma symptoms or brea	athing difficulties if inhaled.
H317 May cause an allergic skin reaction.	
H351 Suspected of causing cancer.	
H335 May cause respiratory irritation.	
H373 May cause damage to organs through prolonge	ed or repeated exposure.

Precautionary statements

ecautionary statement	15
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.

Special labelling of certain mixtures EUH204 Contains is

Contains isocyanates. May produce an allergic reaction.

2.3. Other hazards

Not known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization Preparation with isocyanates



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX S H3

Revision date: 08.06.2017

Product code: 00359-1085

Page 3 of 10

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
9016-87-9	Diphenylmethanediisoc	yanate, isomers and homologues		75 - < 100 %
		kin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1 19 H334 H317 H335 H373	Skin Sens. 1, STOT SE 3, STOT RE	
101-68-8	Diphenylmethane-4,4'-diisocyanate			10 - < 20 %
	202-966-0	615-005-00-9	01-2119457014-47	
		kin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1 19 H334 H317 H335 H373	Skin Sens. 1, STOT SE 3, STOT RE	
5873-54-1	Diphenylmethane-2,4'-diisocyanate			5 - < 15 %
	227-534-9	615-005-00-9	01-2119480143-45	
		kin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1 19 H334 H317 H335 H373	Skin Sens. 1, STOT SE 3, STOT RE	
2536-05-2	Diphenylmethane-2,2'-diisocyanate			0,3 - < 1 %
	219-799-4	615-005-00-9	01-2119927323-43	
		kin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1 19 H334 H317 H335 H373	Skin Sens. 1, STOT SE 3, STOT RE	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately. In the event of persistent symptoms receive medical treatment. Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours. If patient is not breathing, apply artificial respiration. Refer for medical treatment.

After contact with skin

Wash contaminated skin with plenty of water and soap or with liquid polyethylene glycol . Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting. Rinse out mouth thoroughly with water. Summon a doctor immediately. Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX S H3

Revision date: 08.06.2017

Product code: 00359-1085

Page 4 of 10

May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Suspected of causing cancer.

4.3. Indication of any immediate medical attention and special treatment needed

Keep under medical supervision for at least 48 hours. Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce: carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

Hydrogen cyanide (HCN)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator. Ensure adequate ventilation. Remove persons to safety.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water. Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal. Container should not be gas-tight closed. Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Vapours are heavier than air and spread along ground. Avoid contact with the skin and the eyes. Do not breathe vapours.



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX S H3

Revision date: 08.06.2017

Product code: 00359-1085

Page 5 of 10

Local exhaust. Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

Advice on storage compatibility

Exothermic reaction with: Acids and bases. Water, amines, alcohols

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

7.3. Specific end use(s)

Hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
-	Isocyanates, all (as -NCO) Except methyl isocyanate	-	0.02		TWA (8 h)	WEL
		-	0.07		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Take off immediately all contaminated clothing.

Eye/face protection

Tightly fitting goggles (EN 166). Eye wash bottle with pure water (EN 15154).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

Skin protection

Long sleeved clothing (EN 368). Single-use coverall



Test method

according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX S H3

Revision date: 08.06.2017

Product code: 00359-1085

Page 6 of 10

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Musty

Changes in the physical state		
Initial boiling point and boiling range:	> 300 °C	DIN 53171
Pour point:	approx 30 °C	ISO 3016
Flash point:	approx. 229 °C	DIN EN ISO 2719
Lower explosion limits:	n.d.	
Ignition temperature:	> 500 °C	DIN 51794
Vapour pressure: (at 20 °C)	approx. 11 hPa	ECA4
Vapour pressure: (at 50 °C)	approx. 20 hPa	ECA4
Density (at 25 °C):	approx. 1,23 g/cm ³	DIN 51757
Water solubility: (at 20 °C)	Reacts with water.	
Viscosity / dynamic: (at 20 °C)	approx. 145 mPa·s	DIN 53019
2. Other information		

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with strong acids and alkalies. Reacts with: Water, amines, alcohols

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat. [Decomposition temperature $\sim 200^{\circ}$ C] Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

10.5. Incompatible materials

Acids and bases.

Water, amines, alcohols

10.6. Hazardous decomposition products

Hydrogen cyanide gas, Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX S H3

Revision date: 08.06.2017

Product code: 00359-1085

Page 7 of 10

Acute toxicity

Harmful if inhaled. No toxicological data available. Diphenylmethanediisocyanate, isomers and homologues LD50/oral/rat: > 10000 mg/kg [OECD 401] LD50/dermal/rabbit: > 9400 mg/kg [OECD 402]

Irritation and corrosivity

Causes skin irritation. Causes serious eye irritation.

Sensitising effects

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Diphenylmethanediisocyanate, isomers and homologues; Diphenylmethane-4,4'-diisocyanate; Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate) May cause an allergic skin reaction. (Diphenylmethanediisocyanate, isomers and homologues;

Diphenylmethane-4,4'-diisocyanate; Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Diphenylmethanediisocyanate, isomers and homologues; Diphenylmethane-4,4'-diisocyanate; Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Diphenylmethanediisocyanate, isomers and homologues; Diphenylmethane-4,4'-diisocyanate; Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Diphenylmethanediisocyanate, isomers and homologues; Diphenylmethane-4,4'-diisocyanate; Diphenylmethane-2,4'-diisocyanate)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available. Diphenylmethanediisocyanate, isomers and homologues LC50/Danio rerio/96h > 1000 mg/l [OECD 203] EC50/Daphnia magna/48h > 1000 mg/l [OECD 202] EC50/Scenedesmus subspicatus/72h > 1640 mg/l [OECD 201] EC50/Activated sludge/3h > 100 mg/l [OECD 209]

12.2. Persistence and degradability

Biodegradable (OECD): 0% [28 d; OECD 302 C] Not readily biodegradable.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX S H3

Revision date: 08.06.2017

Product code: 00359-1085

Page 8 of 10

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Further information

In aqueous systems, formation of unsoluble and chemically inert (inactive) polyureas. Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

080409

Where possible recycling is preferred to disposal. Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal. Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

 14.2. UN proper shipping name:

 14.3. Transport hazard class(es):

 14.4. Packing group:

 Inland waterways transport (ADN)

 14.1. UN number:

 14.2. UN proper shipping name:

 14.3. Transport hazard class(es):

 14.4. Packing group:

Marine transport (IMDG)

14.1. UN number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX S H3

Revision date: 08.06.2017

Product code: 00359-1085

Page 9 of 10

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

SECTION 15: Regulatory Information				
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture				
EU regulatory information				
Restrictions on use (REACH, annex XV	/II):			
Entry 56: Diphenylmethane-4,4'-diis Diphenylmethane-2,2'-diisocyanate	socyanate; Diphenylmethane-2,4'-diisocyanate;			
2004/42/EC (VOC):	0 %			
National regulatory information				
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.			
Water contaminating class (D):	1 - slightly water contaminating			
15.2. Chemical safety assessment				

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
- CAS = Chemical Abstract Service
- EN = European norm
- ISO = International Organization for Standardization
- DIN = Deutsche Industrie Norm
- PBT = Persistent Bioaccumulative and Toxic
- vPvB = Very Persistent and very Bio-accumulative
- LD = Lethal dose
- LC = Lethal concentration
- EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H315Causes skin irritation.H317May cause an allergic skin reaction.H319Causes serious eye irritation.H322Harmful if inhaled.H334May cause allergy or asthma symptoms or breathing difficulties if inhaled.



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX S H3

Revision date: 08.06.201	7 Product code: 00359-1085	Page 10 of 10
		i ugo io oi io
H335	May cause respiratory irritation.	
H351	Suspected of causing cancer.	
H373	May cause damage to organs through prolonged or repeated exposure.	
EUH204	Contains isocyanates. May produce an allergic reaction.	
(in this sense cons accidents and irre The information de level of our knowle The delivery speci	escribes exclusively the safety requirements for the product(s) and is based on the present	

warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)