REMATIP TOP AG **SOLUTION 12250 D**Revision date: 22 07 20

Revision date: 22.07.2016 Product code: 00156-0437

Revision No: 1,0



Belting Portfolio Manufactured by

# DUNLOP BELTING PRODUCTS (PTY) LTD

Lincoln Road · Benoni 1500 · South Africa

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

SOLUTION 12250 D

**Art.-No.** 538 1350

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

adhesive

#### 1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG
Street: Gruber Strasse 63
Place: D-85586 Poing
Telephone: +49 (0) 8121 / 707 - 0

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

**1.4. Emergency telephone** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements:

May cause an allergic skin reaction.

# 2.2. Label elements

#### Hazard components for labelling

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclioalkanes Signal word: Danger

Pictograms:



## **Hazard statements**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

P273 Avoid release to the environment.
P233 Keep container tightly closed.
P261 Avoid breathing vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P264 Wash hands thoroughly after handling.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

REMA TIP TOP AG

**SOLUTION 12250 D** 

Revision date: 22.07.2016 Product code: 00156-0437

Revision No: 1,0



Belting Portfolio Manufactured by

# **DUNLOP BELTING PRODUCTS (PTY) LTD**

Lincoln Road · Benoni 1500 · South Africa

water/shower.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container to in accordance with local and national regulations.

Special labelling of certain mixtures

EUH208 Contains Di(benzothiazol-2-yl) disulphide. May produce an allergic reaction.

2.3. Other hazards

Vapours may form explosive mixture with air.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Chemical characterization

Preparation in aliphatic hydrocarbons

#### **Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclioalkanes			50 - 100 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
1314-13-2	Zinc oxide			< 1 %
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
120-78-5	Di(benzothiazol-2-yl) disulphide			< 1 %
	204-424-9	613-135-00-0	01-2119489366-24	
	Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410 EUH031			

Full text of H and EUH statements: see section 16.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours.

If you feel unwell, seek medical advice.

## After contact with skin

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

## After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

# After ingestion

Do not induce vomiting.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

REMA TIP TOP AG

**SOLUTION 12250 D** 

Revision date: 22.07.2016 Product code: 00156-0437

Revision No: 1.0



Belting Portfolio Manufactured by

# DUNLOP BELTING PRODUCTS (PTY) LTD

Lincoln Road · Benoni 1500 · South Africa

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways. Attention. Beware, danger of aspiration.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

## Unsuitable extinguishing media

Full water jet.

## 5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide and carbon dioxide

#### 5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

#### **Additional information**

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

#### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Use personal protective clothing.

# 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

# 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

## Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

# Advice on protection against fire and explosion

Do not smoke - volatile.

Keep away from heat and sources of ignition.

REMATIP TOP AG
SOLUTION 12250 D

Revision date: 22.07.2016 Product code: 00156-0437

Revision No: 1.0



Belting Portfolio Manufactured by

# DUNLOP BELTING PRODUCTS (PTY) LTD

Lincoln Road · Benoni 1500 · South Africa

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

# 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

## Advice on storage compatibility

Incompatible with oxidizing agents.

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

## 7.3. Specific end use(s)

adhesive

#### **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

## 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

#### Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

#### Eve/face protection

Tightly fitting goggles (EN 166).

## Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove < Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

#### Skin protection

Solvent-resistant apron (EN 467).

## Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Colourless
Odour: Hydrocarbon-like

### Changes in the physical state

Initial boiling point and boiling range:  $77 \, ^{\circ}\text{C}$  Flash point:  $-1 \, ^{\circ}\text{C}$ 

Explosive properties The product is considered non-explosive; nevertheless explosive vapour/air

mixture can be generated.

REMA TIP TOP AG

**SOLUTION 12250 D** 

Revision date: 22.07.2016 Product code: 00156-0437

Revision No: 1,0



Belting Portfolio Manufactured by

# **DUNLOP BELTING PRODUCTS (PTY) LTD**

Lincoln Road · Benoni 1500 · South Africa

Lower explosion limits:

Upper explosion limits:

11,5 vol. %

Ignition temperature:

460 °C

Vapour pressure:

(at 20 °C)

Density (at 15 °C):

2,1 vol. %

460 °C

97 hPa

< 1 g/cm³

(at 20 °C)

Viscosity / kinematic: < 20,5 mm²/s

(at 40 °C)

Solvent content: > 95 %

9.2. Other information

No data available.

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No decomposition if stored and applied as directed.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

# 10.5. Incompatible materials

oxidizing agents

## 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

# Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclioalkanes)

#### Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

# **Aspiration hazard**

May be fatal if swallowed and enters airways.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no

REMATIP TOP AG

SOLUTION 12250 D Revision date: 22.07.2016

Product code: 00156-0437

Revision No: 1,0



Belting Portfolio Manufactured by

# DUNLOP BELTING PRODUCTS (PTY) LTD

Lincoln Road · Benoni 1500 · South Africa

1272/2008.

## **Practical experience**

#### Other observations

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Hazard of lung oedema.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness,

nausea and vomiting.

Contact with eyes may cause irritation.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties

of the product.

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

Not readily biodegradable.

## 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

# 12.6. Other adverse effects

Hazardous water pollutant.

## **Further information**

Do not flush into surface water or sanitary sewer system.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

## Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS

(PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and

sealants containing organic solvents or other hazardous substances

Classified as hazardous waste.

# Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

#### **SECTION 14: Transport information**

### Land transport (ADR/RID)

<u>14.1. UN number:</u>

UN 1133

14.2. UN proper shipping name: Adhesives

REMATIP TOP AG

SOLUTION 12250 D

Revision date: 22.07.2016 Product code: 00156-0437

Revision No: 1,0



Belting Portfolio Manufactured by

# DUNLOP BELTING PRODUCTS (PTY) LTD

Lincoln Road · Benoni 1500 · South Africa

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Limited quantity: 5 L / 30 kg
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number:UN 113314.2. UN proper shipping name:Adhesives

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label:

3



Classification code: F1

Limited quantity: 5 L / 30 kg
Excepted quantity: E2

Marine transport (IMDG)

**14.1. UN number:** UN 1133

14.2. UN proper shipping name: Adhesives (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Marine pollutant: Yes
Limited quantity: 5 L / 30 kg
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO)

14.1. UN number:UN 113314.2. UN proper shipping name:Adhesives

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Limited quantity Passenger:

SOLUTION 12250 D

REMATIP TOP AG

Revision date: 22.07.2016 Product code: 00156-0437

Revision No: 1,0



Belting Portfolio Manufactured by

# DUNLOP BELTING PRODUCTS (PTY) LTD

Lincoln Road · Benoni 1500 · South Africa

Passenger LQ: Y341 Excepted quantity: E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

### **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

2004/42/EC (VOC): > 95 %

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 2 - water contaminating

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## **SECTION 16: Other information**

## Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

REMA TIP TOP AG

**SOLUTION 12250 D** 

Revision date: 22.07.2016 Product code: 00156-0437

Revision No: 1,0



Belting Portfolio Manufactured by

# **DUNLOP BELTING PRODUCTS (PTY) LTD**

Lincoln Road · Benoni 1500 · South Africa

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.
 Toxic to aquatic life with long lasting effects.
 EUH031 Contact with acids liberates toxic gas.

EUH208 Contains Di(benzothiazol-2-yl) disulphide. May produce an allergic reaction.

#### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)