Revision No: 2,1



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

TIP TOP TYRE SEALANT Art.-No. 593 1040

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Tyre sealing material

1.3. Details of the supplier of the safety data sheet		
Company name:	REMA TIP TOP AG	
Street:	Gruber Strasse 63	
Place:	D-85586 Poing	
Telephone:	+49 (0) 8121 / 707 - 0	
Responsible Department:	Responsible for the safety data sheet: sds@gbk-ingelheim.de	
<u>1.4. Emergency telephone</u> number:	INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a) England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24 24	

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories: Acute toxicity: Acute Tox. 4 Specific target organ toxicity - repeated exposure: STOT RE 2 Hazard Statements: Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure.

## 2.2. Label elements

## Hazard components for labelling

Ethane-1,2-diol Signal word:

Warning

Pictograms:



## Hazard statements

H302 H373	Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure.			
Precautionary staten	nents			
P101	If medical advice is needed, have product container or label at hand.			
P102	Keep out of reach of children.			
P270	Do not eat, drink or smoke when using this product.			
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.			
P330	Rinse mouth.			
P314	Get medical advice/attention if you feel unwell.			
P501	Dispose of contents/container to in accordance with local and national regulations.			
Special labelling of certain mixtures				
EUH208	Contains Colophony. May produce an allergic reaction.			
2.3. Other hazards				

### 2.3. Other hazards

Not known.

## **SECTION 3: Composition/information on ingredients**

Revision date: 18.12.2015 Revision No: 2,1 Product code: 00156-0389



### 3.2. Mixtures

### Chemical characterization Aqueous solution

## Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification according to Regulation (EC) No. 1272/2008 [CLP]				
107-21-1	Ethane-1,2-diol			30 - 60 %	
	203-473-3	603-027-00-1	01-2119456816-28		
	Acute Tox. 4, STOT RE	, STOT RE 2; H302 H373			
8050-09-7	Colophony	< 1 %			
	232-475-7	650-015-00-7	01-2119480418-32		
	Skin Sens. 1; H317				

Full text of H and EUH statements: see section 16.

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### **General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

## After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

## After contact with skin

Wash off with soap and plenty of water. Consult a doctor if skin irritation persists.

### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

## After ingestion

Do not induce vomiting. Rinse out mouth and give plenty of water to drink. Never give anything by mouth to an unconscious person. Call a physician immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

### Harmful if swallowed.

May cause damage to organs through prolonged or repeated exposure. May cause sensitization of susceptible persons by skin contact.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

## Suitable extinguishing media

Fire-extinguishing activities according to surrounding. Foam, carbon dioxide (CO2), dry chemical, water-spray.

## Unsuitable extinguishing media

Full water jet.

## 5.2. Special hazards arising from the substance or mixture

Fire may produce: Carbon monoxide and carbon dioxide

## 5.3. Advice for firefighters

Use breathing apparatus with independent air supply. Protective suit.

Revision date: 18.12.2015 Product code: 00156-0389





### Additional information

Cool containers at risk with water spray jet. Fire residues and contaminated firefighting water must be disposed of in accordance with the local

regulations.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective clothing. High risk of slipping due to leakage/spillage of product.

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water. Do not discharge into the subsoil/soil.

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

## 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

### Advice on safe handling

Keep container tightly closed. Avoid contact with the skin and the eyes.

## Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

### Advice on storage compatibility

Incompatible with oxidizing agents.

## Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

## 7.3. Specific end use(s)

Tyre sealing material

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	WEL
		40	104		STEL (15 min)	WEL
8050-09-7	Rosin-based solder flux fume	-	0.05		TWA (8 h)	WEL
		-	0.15		STEL (15 min)	WEL

## 8.2. Exposure controls

## Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

## Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and at the end of workday.

Revision date: 18.12.2015 Revision No: 2,1 Product code: 00156-0389



When using do not eat, drink or smoke. Remove and wash contaminated clothes before re-use.

Eye/face protection

Safety goggles with side protection (EN 166).

## Hand protection

Protective gloves resistant to chemicals made off natural-rubber latex, minimum coat thickness 0.6 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Lapren 706> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

### Skin protection

Long sleeved clothing (EN 368).

## **Respiratory protection**

No personal respiratory protective equipment normally required.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	
Odour:	Soft
pH-Value:	7,9
Changes in the physical state	
Melting point:	n.d.
Initial boiling point and boiling range:	n.d.
Flash point:	> 100 °C
Lower explosion limits:	n.d.
Upper explosion limits:	
Ignition temperature:	n.d.
Vapour pressure:	n.d.
Density (at 20 °C):	n.d.
Water solubility: (at 20 °C)	Miscible
9.2. Other information	

No data available.

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No decomposition if stored and applied as directed.

## 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

## 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Revision date: 18.12.2015 Product code: 00156-0389 Revision No: 2,1



## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

### Acute toxicity

Harmful if swallowed. No toxicological data available. Ethane-1,2-diol LD50/oral/rat: 5840 mg/kg LD50/dermal/rabbit: 9530 mg/kg LC50/inhalation/rat: 50200 mg/m³/8 h LD/oral/human: 398 mg/kg

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### Severe effects after repeated or prolonged exposure

May cause damage to organs through prolonged or repeated exposure. (Ethane-1,2-diol )

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

## Practical experience

### Other observations

Repeated or prolonged exposure may cause irritation of eyes and skin. May cause sensitization of susceptible persons by skin contact. Inhalation of vapours may cause mild irritation to the mucous membranes.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Ecological data are not available. Ethane-1,2-diol LC50/Oncorhynchus mykiss/96 h = 40761 mg/l EC50/Daphnia magna/48 h = 41100 mg/l

## 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data available.

## 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

### 12.6. Other adverse effects

Low hazard to waters.

### **Further information**

Ecological injuries are not known or expected under normal use. Do not flush into surface water or sanitary sewer system.

## **SECTION 13: Disposal considerations**

Revision date: 18.12.2015 Revision No: 2,1 Product code: 00156-0389



## 13.1. Waste treatment methods

### Advice on disposal

080409

Where possible recycling is preferred to disposal. Can be incinerated, when in compliance with local regulations.

### Waste disposal number of waste from residues/unused products

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances Classified as hazardous waste.

### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

## **SECTION 14: Transport information**

## Land transport (ADR/RID); Marine transport (IMDG); Air transport (ICAO); Inland waterways transport (ADN):

### 14.1. UN number:

No hazardous material as defined by the transport regulations.

### 14.2. UN proper shipping name:

No hazardous material as defined by the transport regulations.

## 14.3. Transport hazard class(es):

No hazardous material as defined by the transport regulations.

#### 14.4. Packing group:

No hazardous material as defined by the transport regulations.

### 14.5. Environmental hazards

No hazardous material as defined by the transport regulations.

### 14.6. Special precautions for user

No hazardous material as defined by the transport regulations.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No hazardous material as defined by the transport regulations.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information	
2004/42/EC (VOC):	0 %
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water contaminating class (D):	1 - slightly water contaminating
15.2. Chemical safety assessment	

For this substance a chemical safety assessment has not been carried out.

## **SECTION 16: Other information**

### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

### TIP TOP TYRE SEALANT

Revision date: 18.12.2015 Revision Product code: 00156-0389

Revision No: 2,1



REACH = Registration, Evaluation, Authorization and Restriction of Chemicals CAS = Chemical Abstract Service EN = European norm ISO = International Organization for Standardization DIN = Deutsche Industrie Norm PBT = Persistent Bioaccumulative and Toxic vPvB = Very Persistent and very Bio-accumulative LD = Lethal dose LC = Lethal concentration EC = Effect concentration IC = Median immobilisation concentration or median inhibitory concentration Relevant H and EUH statements (number and full text) Harmful if swallowed. H302 H317 May cause an allergic skin reaction. H373 May cause damage to organs through prolonged or repeated exposure. EUH208 Contains Colophony. May produce an allergic reaction. **Further Information** Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the

legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Print date: 18.12.2015