



// ONE BRAND // ONE SOURCE // ONE SYSTEM

CORGHI EM9350 X Line

- Dynamic balancing on both sides of the rim
- 7 ALU programmes (5 statistical ALUs + 2 ALU P)
- Motorcycle dynamic • Motorcycle ALU
- Static
- OPT flash
- Hidden Weight in ALU P
- Split Weight in motorcycle programmes
- "Shift Planes" Programme in ALU P
- Display of the unbalance in grams or ounces
- Automatic balancing

Standard accessories:

- Pliers for application of the counterweights
- Callipers for measuring wheel width
- Sample weight calibration
- 7 short accessory holder sleeves and 2 flange holder sleeves
- Centring kit. Composed of 181 mm threaded hub, cones and quick ring nut



Balancing speed	90 - 130 rpm
Resolution	0.0353 oz (1 g)
Shaft diameter	1.57 Inch (40 mm)
Rim width setting range	1.5 - 20 Inch
Rim diameter setting range	1 - 35 Inch
Rim diameter measurable with sensor	11 - 28 Inch
Max. wheel width (with guard)	23.5 Inch (600 mm)
Max. wheel diameter (with guard)	44 Inch (1117 mm)
Max. wheel/machine distance	10.82 Inch (275 mm)
Max. wheel weight with fixing to the ground	165 lbs (75 kg)
Max. wheel weight with supporting foot	165 lbs (75 kg)
Power supply	1230v/1ph/50hz
Max. dimensions l x d x h	1605 x 1165 x 1650 mm

- FINANCE OPTIONS**
- SERVICE CONTRACTS**
- ACCESSORIES**
- 2 YEAR WARRANTY**
- FREE DELIVERY AND INSTALLATION**

T. 07860 449436
T. 0113 2770044

exclusively distributed by REMA TIP TOP in Great Britain



REMA TIP TOP AUTOMOTIVE UK LIMITED
Westland Square · Leeds · West Yorkshire · LS11 5XS
Phone: +44 (0)113 385 8606
Fax: +44 (0)113 277 6200
info@tip-top.co.uk
www.rema-tiptop.co.uk



Aftermarket Equipment Supplier of the Year

WINNERS 2014, 2015, 2016, 2017

