

"ONE BRAND "ONE SOURCE "ONE SYSTEM



#SERVICE #MATERIAL PROCESSING #SURFACE PROTECTION #AUTOMOTIVE

CORGHI A2025TYRE CHANGER



CORGHI A2025

- The turntable installed as standard uses a patented system allowing work on all tyre types from 10" to 24" - changing the working range from 10"- 20" to 14" - 24" by a simple operator procedure.
- New shape designed to assure users working on large diameter wheels easier and quicker wheel positioning during bead breaking; and above all the minimisation of the size of the plate fitted to the machine. Turntable 675 mm above the
- The bead breaker installed fitted with a new component which allows the length of the fixed arm shoe to be extended. It also ensures that the bead breaker shoe is always in exactly the right position in relation to the wheel, ruling out the risk of damage to the tyre and/or rim.
- Dual-position telescopic rim support is extremely useful for breaking the beads of all types of wheel up to a maximum width of 14".
- Sliding supports with interchangeable clamping zones. Taller cast clamps for better rim clamping from inside and outside. Clamps inside and outside fully protected with plastic protectors to avoid damaging the more delicate rims.
- Simultaneous pneumatic locking of horizontal and vertical head arms, with automatic head positioning in the ideal working position.

lance elementary appeals.	10 00 leads
Inner clamping capacity	13 - 26 Inch
Outer clamping capacity	10 - 24 Inch
Maximum tyre diameter	1100 mm
Maximum tyre width	360 mm (14")
Rotation torque	1200 Nm
DV version rotation torque	1300 Nm)
Rotation speed	8 rpm
DV version rotation speed	6 - 15 rpm
Height above the ground	675 mm
Bead breaker opening	380 mm
Operating pressure	10 bar
Weight	259 kg
Power supply	230v/1ph/50hz & 400v/3ph/50hz
	& 200-230v/1ph/DV

Ref. No.	Description	Content
A2025	CORGHI A2025	1
A2025DV	CORGHI A2025DV	1
A2025TI	CORGHI A2025TI	1





T. 07860 449436



REMA TIP TOP AUTOMOTIVE UK LIMITED

Westland Square · Leeds · West Yorkshire · LS11 5XS

Phone: +44 (0)113 385 8606 Fax: +44 (0)113 277 6200 info@tip-top.co.uk

www.rema-tiptop.co.uk













